

[1] LOCATION OF WATER WELL:		Fraction	Township Number	Range Number
County: MORTON		SW ¼ SE ¼ SW ¼	25 T 34 S	R 40 E/W
Distance and direction from nearest town or city street address of well if located within city? 4 MILES SOUTH & ½ MILE EAST FROM ROLLA.				
[2] WATER WELL OWNER:				
RR#, St. Address, Box # :		CLARK LITTELL 109 WEST 6TH		
City, State, ZIP Code :		HUGOTON, KS 67951		
		Board of Agriculture, Division of Water Resources Application Number: 41,785		
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		[4] DEPTH OF COMPLETED WELL 460 . . . ft. ELEVATION:		
 N W E S NW NE SW SE X		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 190 . . . ft. below land surface measured on mo/day/yr 2/10/97 Pump test data: Well water was ft. after . . . hours pumping . . gpm Est. Yield gpm: Well water was ft. after . . . hours pumping . . gpm Bore Hole Diameter . . 26 . . in. to . . 460 . . ft., and . . in. to . . ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes.....No... <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No		
		[5] TYPE OF BLANK CASING USED:		
		Blank casing diameter . . . 16 . . in. to . . 460 . . ft., Dia . . in. to . . ft., Dia . . in. to . . ft. Casing height above land surface . . . 12 . . in., weight . . 42.5 . . lbs./ft. Wall thickness or gauge No. . . 250 . .		
		TYPE OF SCREEN OR PERFORATION MATERIAL:		
		SCREEN OR PERFORATION OPENINGS ARE:		
Type of Screen or Perforation Material: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		Type of Casing Joint: Glued Clamped Welded Threaded		
2 PVC 4 ABS 6 Concrete tile 9 ABS		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
3 Mill slot 4 Key punched 7 Torch cut 10 Other (specify)		8 Saw cut 11 None (open hole)		
From SCREEN 280 ft. to 300 ft.		From PERF 300 ft. to 350 ft.		
From SCREEN 350 ft. to 370 ft.		From PERF 370 ft. to 400 ft.		
GRAVEL PACK INTERVALS: From 20 ft. to 460 ft.		From SCREEN 400 ft. to 460 ft.		
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS		
0	200	o4 SURFACE, SAND & CLAY		
200	240	o7 FINE SAND		
240	280	o4 BROWN CLAY W/FINE SAND		
280	340	o1 SOFT STICKY CLAY W/FINE SAND		
340	440	o7 MED. FINE SAND		
440	460	o4 FIRM MED. SAND W/CLAY STRIPS		
460	480	o1 FIRM BROWN & RED CLAY		
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/5/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 225 This Water Well Record was completed on (mo/day/yr) 5/14/97 under the business name of KIM DRILLING, INC. by (signature) [Signature]				

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.