

WATER WELL RECORD Form WWC-5 KSA 82a-1212 **Plugging Report**

1 LOCATION OF WATER WELL: County: Morton Fraction 1/4 1/4 1/4 SWNE 15 Township Number T 34 Range Number R 41 EW

Distance and direction from nearest town or city street address of well if located within city?
1/4 mile on 56 1/2 N 1/2 E Elkhart KS

2 WATER WELL OWNER: U.S. Forrest Service

RR#, St. Address, Box # :
City, State, ZIP Code : Elkhart KS 67950

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 250 ft. ELEVATION: 138 ft.

Depth(s) Groundwater Encountered 1 ft. 2. 138 ft. 3. 250 ft.

WELL'S STATIC WATER LEVEL 138 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 1 ft. after 138 hours pumping 138 gpm

Est. Yield 138 gpm: Well water was 1 ft. after 138 hours pumping 138 gpm

Bore Hole Diameter WAS in. to 138 ft., and 250 in. to 250 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No No No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No No No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued No Clamped No
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded No
2 PVC 4 ABS 7 Fiberglass Threaded No

Blank casing diameter 5 1/2 in. to 138 ft., Dia 138 in. to 250 ft., Dia 250 in. to 250 ft.

Casing height above land surface 3 in., weight Below lbs./ft. Wall thickness or gauge No. 7 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) Not Available

SCREEN-PERFORATED INTERVALS: From N/A ft. to N/A ft., From 138 ft. to 250 ft.

GRAVEL PACK INTERVALS: From 138 ft. to 250 ft., From 138 ft. to 250 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 138 ft. to 138 ft., From 138 ft. to 250 ft., From 250 ft. to 250 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage NONE

Direction from well? NONE How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			0	3	Top soil
			3	138	Cement
			138	138	Bentonite
			138	250	Sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-6-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 10-6-92 This Water Well Record was completed on (mo/day/yr) 10-6-92 under the business name of Stowells Water Well Service, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.