

1) LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Morton		SW 1/4 NE 1/4 SW 1/4		33		T 34 S		R 41 E/W	
Distance and direction from nearest town or city street address of well if located within city? 2 1/4 South 1/2 West of Wilburton, Ks.									
2) WATER WELL OWNER: WMSU		Cities Service							
RR#, St. Address, Box # :		3545 NW 58th Street							
City, State, ZIP Code :		Oklahoma City, Ok. 73112							
		Board of Agriculture, Division of Water Resources							
		Application Number: T83-423							
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: 250 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 85 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 165 ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter in. to ft. and in. to ft.							
		WELL WATER TO BE USED AS:							
		1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well							
		2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)							
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5) TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile							
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Welded							
		7 Fiberglass Threaded							
Blank casing diameter 5 in. to 170 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 165 ft. to 250 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 155 ft. to 250 ft. From ft. to ft.									
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout intervals: From ft. to ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? Southeast		How many feet? 220							
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG							
250 175 Sand 21 C. Ft.									
175 165 Cement 2.77 C. Ft.									
165 13 Sand 42 C. Ft.									
13 3 Cement 2.77 C. Ft.									
3 0 Dirt .33 C. Ft.									
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-21-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) under the business name of T & W Water Well Service, Inc. by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									