

1 LOCATION OF WATER WELL: COUNTY: MORTON		Fraction SW 1/4 SW 1/4 SE 1/4	Section Number 4	Township Number T 34 S	Range Number R 41 W												
Distance and direction from nearest town or city street address of well if located within city? FROM WILBURTON, KS. - 3 MILES NORTH AND 1/2 MILE WEST																	
2 WATER WELL OWNER: TUCKER, JOHN RR#, St. Address, Box # : 228 N. BACA City, State, ZIP code : ELKHART, KS 67950-		Board of Agriculture, Division of Water Resources Application Number:															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 195 ELEVATION: 0 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.															
<div style="display: flex; align-items: center;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg); margin-right: 5px;">1 mile</div> <table border="1" style="border-collapse: collapse; text-align: center;"> <tr><td> </td><td>NW</td><td>NE</td></tr> <tr><td>W</td><td> </td><td> </td></tr> <tr><td> </td><td>SW</td><td>SE</td></tr> <tr><td> </td><td> </td><td>X</td></tr> </table> </div>			NW	NE	W				SW	SE			X	WELL'S STATIC WATER LEVEL 70 ft. below land surface measured on mo/day/yr 09/12/94 Pump testdata: Well water was 0 ft. after 0 hours pumping 0 gpm			
			NW	NE													
		W															
			SW	SE													
		X															
Estimated Yield 25 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm																	
Bore Hole Diameter 9 in. to 195 ft., and in. to 0 ft.																	
		WELL WATER TO BE USED AS: DOMESTIC															
		Was a chemical/bacteriological sample submitted to department? No ; If yes, mo/day/yr sample was submitted Water well disinfected? Yes															
5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED Blank casing diameter 5 in. to 195 ft., Dia in. to 0 ft., Dia in. to 0 ft. Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC SCREEN OR PERFORATION OPENINGS ARE: SAW CUT																	
SCREEN PERFORATED INTERVALS: From 170 ft. to 190 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. GRAVEL PACK INTERVALS: From 20 ft. to 195 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft.																	
6 GROUT MATERIAL BENTONITE Grout Intervals: From 0 ft. to 20 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft. What is the nearest source of possible contamination: NONE Direction from well? How many feet? 0																	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS												
0	25	TOPSOIL BROWN CLAY SANDY CLAY															
25	44	MEDIUM SAND															
44	50	BROWN CLAY															
50	80	MED-COARSE SAND GRAVEL CLAY															
80	90	MEDIUM SAND VERY LOOSE BROWN CLAY															
90	118	CALACHIE CLAY															
118	140	BROWN CLAY															
140	155	SANDSTONE															
155	190	SANDSTONE CLAY															
190	200	BED BED															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 09/12/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 10/10/94, under the business name of JOE'S WELL SERVICE, INC. by (signature) <i>Inside Creek</i>																	