


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: MORTON		1/4 C/NE 1/4 NE 1/4	36	T 34 S	R 42W EW
Distance and direction from nearest town or city street address of well if located within city? FROM WILBURTON 4 W, 3/4 N WEST INTO LOC.					
2 WATER WELL OWNER: BIG "A" DRILLING		<i>Bennett B-5</i> Board of Agriculture, Division of Water Resources Application Number: 950041			
RR#, St. Address, Box #: BOX 1856					
City, State, ZIP Code: LIBERAL, KS 67905-1856					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 260 ft. ELEVATION: 108 ft.			
<div style="text-align: center;"></div>		Depth(s) Groundwater Encountered 1. 108 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 108 ft. below land surface measured on mo/day/yr 1-19-95			
		Pump test data: Well water was 120 ft. after 1 hours pumping 100 gpm			
		Est. Yield 100 gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 11 in. to 260 ft. and in. to ft.		WELL WATER TO BE USED AS:			
5 Public water supply		8 Air conditioning		11 Injection well	
1 Domestic		3 Feedlot		9 Dewatering	
2 Irrigation		4 Industrial		12 Other (Specify below)	
7 Lawn and garden only		10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 6 in. to 260 ft. Dia		in. to ft. Dia		in. to ft. Dia	
Casing height above land surface 24 in. weight 2.902 lbs./ft.		Wall thickness or gauge No. 280 SDR 21			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		3 Mill slot		6 Wire wrapped	
2 Louvered shutter		4 Key punched		7 Torch cut	
SCREEN-PERFORATED INTERVALS:		From 180 ft. to 260 ft.		From ft. to ft.	
GRAVEL PACK INTERVALS:		From 140 ft. to 260 ft.		From ft. to ft.	
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
4 Other		HOLE PLUG			
Grout intervals: From 1 ft. to 20 ft.		From ft. to ft.		From ft. to ft.	
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
10 Livestock pens		14 Abandoned water well		15 Oil well/Gas well	
11 Fuel storage		12 Fertilizer storage		16 Other (specify below)	
13 Insecticide storage		How many feet? 300			
Direction from well? Northwest					
FROM TO		LITHOLOGIC LOG		FROM TO	
0 7		SANDY CLAY			
7 14		BROWN CLAY			
14 33		SANDY CLAY			
33 42		SAND & GRAVEL			
42 93		SANDY CLAY & SAND STONE			
93 115		CLAY			
115 147		SANDY CLAY			
147 174		FINE SAND W/SANDY CLAY STREAKS			
174 182		SANDY CLAY			
182 230		FINE SAND & SAND & GRAVEL			
230 260		RED SANDY CLAY & RED SAND STONE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-19-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/year) 1-19-95 under the business name of HOWARD DRLG.CO.BOX 806 BEAVER, OK 73932 by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					