


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Morton	C 1/4 NW 1/4 SE 1/4	24	T 34 S	R 42 EW

Distance and direction from nearest town or city street address of well if located within city?

3 1/4 miles W of Wilburton, KS--

2 WATER WELL OWNER:	OXY USA, Inc.	#3 Brown-E
RR#, St. Address, Box # :	P.O. Box 26100	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Oklahoma City, OK 73126-0100	Application Number: OXY permitted

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 280 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 125 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 125 ft. below land surface measured on mo/day/yr 10-16-91
	Pump test data: Well water was 167 ft. after 1 hours pumping 75 gpm
	Est. Yield 75 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 9 1/2 in. to 280 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well
	2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 280 ft., Dia			11 Other (specify)
Casing height above land surface 24 in., weight			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From 200 ft. to 280 ft.			
GRAVEL PACK INTERVALS:			
From 180 ft. to 280 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Hole plug
Grout Intervals: From 1 ft. to 20 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? Southeast				
How many feet? 250				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil	274	280	Redbed
3	10	Clay			
10	29	Sandy Clay			
29	132	Sand and Large Gravel			
132	157	Sandy Clay			
157	190	Fine Sand w/Clay Streaks			
190	208	Sandy Clay			
208	216	Sand			
216	221	Sandy Clay			
221	236	Sand			
236	244	Clay			
244	256	Sand			
256	262	Clay			
262	268	Fine Sand			
268	274	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-16-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 10-16-91 under the business name of Howard Drlg.Co. Box 806 Beaver, OK 73932 by (signature)
--