

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:

Section-Township-Range: _____

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): _____County: MortonLocation ~~changed to~~:8-345-43 WSE SW SEOther changes: Initial statements: From Elkhart; appx. 7 miles South & 7 miles West.Changed to: From Elkhart; approx. 6 mi. N., 6 mi. W.

Comments: _____

verification method: Legal description, other Anadarko monitoring wells
in the vicinity, and Elkhart North & Midway SE 1:24,000
topo. maps. initials: DR date: 1/13/2006

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726

to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

MW 7

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 COUNTY: 065 MORTON SE 1/4 SW 1/4 SE 1/4 08 T 34 S R 43 W

Distance and direction from nearest town or city street address of well if located within city?
 FROM ELKHART; APPX 7 MILES SOUTH & 7 MILES WEST

2 WATER WELL OWNER: ANADARKO PETROLEUM
 RR#, St. Address, Box # : 5231 S. QUEBEC ST Board of Agriculture, Division of Water Resources
 City, State, ZIP code : GREENWOOD VILLAGE, CO 80111-1802 Application Number: |

3 LOCATE WELL'S LOCATION WITH
 AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL 221 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.

WELL'S STATIC WATER LEVEL 126 ft. below land surface measured on mo/day/yr 08/16/05
 Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm

Estimated Yield 0 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm

Bore Hole Diameter 6 in. to 221 ft., and in. to 0 ft.

WELL WATER WAS: 10 - MONITORING

Was a chemical/bacteriological sample submitted to department? No ;
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: 01 STEEL CASING JOINTS: WELDED
 Blank casing diameter 5 in. to 221 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface -36 in., weight 15 lbs/ft. Wall thickness or gauge No. .258
 TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL
 SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SLOT

SCREEN PERFORATED INTERVALS: From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL 02 CEMENT GROUT
 Grout Intervals: From 3 ft. to 22 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: NONE OBSERVED
 Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			3	221	CEMENT GROUT
			3	0	BACKFILL
			0	0	
			0	0	
			0	0	
			0	0	
			0	0	
			0	0	
			0	0	
			0	0	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Plugged under my jurisdiction and was
 completed on (mo/day/year) 08/16/05 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 09/08/05
 under the business name of HENKLE DRILLING & SUPPLY by (signature) *Bryan J. Richmond*