LOCATION OF WATER WELL: Fraction COUNTY: 065 MORTON NE 1/4 SW 1/4 SE	Section Number
Distance and direction from nearest town or city stree APPROX. 6 MILES WEST AND 6 1/4 MILES NORTH OF ELKHART.	
WATER WELL OWNER: ANADARKO PRODUCTION CO. RR#, St. Address, Box # : P.O. BOX 351	Board of Agriculture, Division of Water Resources
City, State, ZIP code : LIBERAL, KS 67901-	Application Number:
LOCATE WELL'S LOCATION WITH	PLETED WELL 155 ELEVATION: 0 undwater Encountered 1. 130 ft. 2. 0 ft. 3. 0
	WATER LEVEL 130 ft. below land surface measured on mo/day/yr 06/12/ testdata: Well water was 0 ft. after 0 hours pumping 0
	d Ogpm: Well water was Oft, after Ohours pumping O
	eter 9.875 in. to 192 ft., and in. to 0 ft.
e	BE USED AS: 04 INDUSTRIAL
X Was a chemical	/bacteriological sample submitted to department? No ;
TYPE OF BLANK CASING USED: 02 PVC CASE Blank casing diameter 5 in. to 155 ft., December 12 in., weight	ING JOINTS: GLUED ia in. to 0 ft., Dia in. to 0 ft.
TYPE OF BLANK CASING USED: 02 PVC CASE Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft.	ING JOINTS: GLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 02 PVC CAS: Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft.: From 0 ft.:	ING JOINTS: GLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 155 ft., From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 02 PVC CAS. Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft.: From 0 ft.: GRAVEL PACK INTERVALS: From 25 ft.: From 0 ft.:	ING JOINTS: SLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. 155 ft. to 192 ft., From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 02 PVC CAS. Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft. From 0 ft. GRAVEL PACK INTERVALS: From 25 ft. From 0 ft. GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to 25 ft., From What is the nearest source of possible contamination: Direction from well? LOCAL AREA	ING JOINTS: SLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 02 PVC CAS Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft. From 0 ft. GRAVEL PACK INTERVALS: From 25 ft. From 0 ft. GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to 25 ft., From What is the nearest source of possible contamination: Direction from well? LOCAL AREA	ING JOINTS: SLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. How many feet?
TYPE OF BLANK CASING USED: 02 PVC CAS Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weigh TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft. From 0 ft. GRAVEL PACK INTERVALS: From 25 ft. From 0 ft. GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to 25 ft., From What is the nearest source of possible contamination: Direction from well? LOCAL AREA FROM ; TO ; LITHOLOGIC LOG 0; 2; 01 CLAY 2; 4; 04 SANDY CLAY 4; 9; 07 FINE SAND 08 MEDIUM SAND 09 CO	ING JOINTS: GLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. ### How many feet? FROM TO PLUGGING INTERVALS
TYPE OF BLANK CASING USED: 02 PVC CAS Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weigh TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft. From 0 ft. GRAVEL PACK INTERVALS: From 25 ft. From 0 ft. GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to 25 ft., From What is the nearest source of possible contamination: Direction from well? LOCAL AREA FROM	ING JOINTS: GLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. How many feet? FROM TO PLUGGING INTERVALS ARSE SAND D
TYPE OF BLANK CASING USED: 02 PVC CAS: Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft. From 0 ft. GRAVEL PACK INTERVALS: From 25 ft. From 0 ft. GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to 25 ft., From What is the nearest source of possible contamination: Direction from well? LOCAL AREA FROM	ING JOINTS: GLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. How many feet? FROM TO PLUGGING INTERVALS ARSE SAND D
TYPE OF BLANK CASING USED: 02 PVC CAS: Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft.: From 0 ft.: GRAVEL PACK INTERVALS: From 25 ft.: From 0 ft.: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to 25 ft., From What is the nearest source of possible contamination: Direction from well? LOCAL AREA FROM	ING JOINTS: GLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. How many feet? FROM TO PLUGGING INTERVALS ARSE SAND D
TYPE OF BLANK CASING USED: 02 PVC CAS: Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft. From 0 ft. GRAVEL PACK INTERVALS: From 25 ft. From 0 ft. GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to 25 ft., From What is the nearest source of possible contamination: Direction from well? LOCAL AREA FROM ; TO ; LITHOLOGIC LOG 0; 2; 01 CLAY 2; 4; 04 SANDY CLAY 4; 9; 07 FINE SAND 08 MEDIUM SAND 09 COG 9; 84; 04 SANDY CLAY 05 SAND 132; 153; 04 SANDY CLAY 05 SAND 132; 153; 07 FINE SAND 08 MEDIUM SAND 153; 158; 04 SANDY CLAY	ING JOINTS: GLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. How many feet? FROM TO PLUGGING INTERVALS ARSE SAND D
TYPE OF BLANK CASING USED: 02 PVC CAS. Blank casing diameter 5 in. to 155 ft., D: Casing height above land surface 12 in., weight TYPE OF SCREEN OR PERFORATION MATERIAL: 07 PVC SCREEN OR PERFORATION OPENINGS ARE: 03 MILL SLOT SCREEN PERFORATED INTERVALS: From 140 ft. From 0 ft. GRAVEL PACK INTERVALS: From 25 ft. From 0 ft. GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to 25 ft., From What is the nearest source of possible contamination: Direction from well? LOCAL AREA FROM	ING JOINTS: GLUED ia in. to 0 ft., Dia in. to 0 ft. ht 3 lbs/ft. Wall thickness or gauge No265 to 155 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. to 0 ft., From 0 ft. to 0 ft. How many feet? FROM TO PLUGGING INTERVALS ARSE SAND D

completed on (mo/day/year) 10/10/91 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 145

Under the business name of HENKLE DRILLING & SUPPLY

Water Well Record was completed on (mo/day/yr) 01/13/92

Under the business name of HENKLE DRILLING & SUPPLY

Water Well Record was completed on (mo/day/yr) 01/13/92

Under the business name of HENKLE DRILLING & SUPPLY

Water Well Record was completed on (mo/day/yr) 01/13/92

Under the business name of HENKLE DRILLING & SUPPLY

Water Well Record was completed on (mo/day/yr) 01/13/92

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: ; Fraction ; Section Number ! Township Number : Range Number ! NE 1/4 SW 1/4 SE 1/4 ; 08 COUNTY: 065 MORTON ; T 34 S ; R 43 2 WATER WELL OWNER: ANADARKO PRODUCTION CO. ; RR#, St. Address, Box # : P.O. BOX 351 Board of Agriculture, Division of Water Resources City, State, ZIP code : LIBERAL, KS 67901-Application Number: FROM : LITHOLOGIC LOG 215 : 19 SHALE 211

!7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Reconstructed under my jurisdiction and was completed on (mo/day/year) 10/10/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 01/13/92 under the business name of HENKLE DRILLING & SUPPLY by (signature)