

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

MW-2


Original Record Correction Change in Well Use

Well ID

1 LOCATION OF WATER WELL: County: Harper Fraction SW 1/4 SW 1/4 SW 1/4 SW 1/4 Section Number 25 Township Number T 34 S Range Number R 8 E W

2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: Business: Energy Transfer/Rose Rock Midstream Partners Address: 8801 S. Yale Ave. Ste. 310 NE Corner of SW 60th Avenue and SW 70th Road Anthony, KS 67150 City: Tulsa State: OK ZIP: 74137

3 LOCATE WELL WITH "X" IN SECTION BOX: N



4 DEPTH OF COMPLETED WELL: 20.0 ft. Depth(s) Groundwater Encountered: 1) 16.5 ft. 2) ft. 3) ft. or 4) Dry Well WELL'S STATIC WATER LEVEL: 16.84 ft. below land surface, measured on (mo-day-yr) 1/26/2023 Pump test data: Well water was 8.25 hours pumping 20.0 gpm Well water was 20.0 hours pumping gpm Estimated Yield: gpm Bore Hole Diameter: 8.25 in. to 20.0 ft. and in. to ft.

5 Latitude: 37.050938 (decimal degrees) Longitude: -98.145993 (decimal degrees) Horizontal Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model): (WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper: Google Earth

6 Elevation: 1293 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other Google Earth

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock 2. Irrigation 3. Feedlot 4. Industrial 5. Public Water Supply: well ID 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID 8. Monitoring: well ID MW-2 9. Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 10. Oil Field Water Supply: lease 11. Test Hole: well ID Cased Uncased Geotechnical 12. Geothermal: how many bores? a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 2 in. to 10.0 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 30 in. Weight lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 10.0 ft. to 20.0 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 8.0 ft. to 20.0 ft., From ft. to ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Concrete U-2 feet Grout Intervals: From 2.0 ft. to 8.0 ft., From ft. to ft., From ft. to ft.

Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Pipeline Release Direction from well? Adjacent Distance from well? 0 ft.

Table with columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Includes a 'Notes' section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 1/25/2023 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 759 This Water Well Record was completed on (mo-day-year) 4/16/2023 under the business name of RAZEK Environmental, LLC Signature



STRATIGRAPHIC AND INSTRUMENTATION LOG (OVERBURDEN)

PROJECT NAME: ETC Anthony Release

HOLE DESIGNATION: B-2 (MW-2)

PROJECT NUMBER: 12569986

DATE COMPLETED: 25 January 2023

CLIENT: Energy Transfer Partners

DRILLING METHOD: 8.25" OD HSA

LOCATION: Anthony, Kansas

FIELD PERSONNEL: J. Raye

File: \\GHDNET\GHD\USTOPEKA\PROJECTS\6312569986\TECH\GIN\112569986-2023.GPJ Library File: GHD_ENVIRO_V08.GLB Report: OVERBURDEN LOG Date: 26/2/23

DEPTH ft BGS	STRATIGRAPHIC DESCRIPTION & REMARKS	DEPTH BGS	MONITOR INSTALLATION	SAMPLE				
				NUMBER	INTERVAL	REC (%)	'N' Value	PID (ppm)
2	ML-SILT (FILL), with clay, stiff, low plasticity, dark reddish brown, slight moisture, massive		<p>Concrete</p> <p>Bentonite</p> <p>Sand Pack</p> <p>Well Screen</p>	1	P/S	100		0.0
4				2	P/S	100		0.0
10	ML-SILT (NATIVE), with clay, stiff, low plasticity, reddish brown, slight moisture, massive	10.00		3	P/S	100		
14			13.25					1343
16	ML-SILT, with some clay, friable, stiff, low plasticity, reddish brown with tan to gray mottling - becomes very moist, soft at 15.00ft BGS - very stiff, massive at 15.75ft BGS - Refusal at 16.00ft BGS END OF BOREHOLE @ 16.00ft BGS	16.00		4	P/S	100		180.7
18								

COMPLETION DETAILS

Screened interval:
10.00 to 20.00ft BGS
Length: 10ft
Diameter: 2in
Slot Size: #10
Material: PVC
Sand Pack:
8.00 to 20.00ft BGS
Material: Silica

NOTES: MEASURING POINT ELEVATIONS MAY CHANGE; REFER TO CURRENT ELEVATION TABLE

CHEMICAL ANALYSIS