					MW-16					
WATER WELL RECORD Form WWC-5					Division of Water Resources App. No.					
1 LOCATION OF WATER WELL:			Fraction	1. Cal	Section Nu		Township No.	Range Number		
County: Barber			1/4 NW1/4 NW	1 1/4 7W 1/4	Clobal Positioning System (GPS) information:					
Street	Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here						Latitude: \$7.0573 (in decimal degrees)			
	Site is located along Aetna Rd. approximately 14 miles south of					Longitude: 98.9644 (in decimal degrees)				
Aetna Rd. and Hwy 160.					Elevation:					
2 WATER WELL OWNER: ConocoPhillips					Datum: WGS 84, NAD 83, NAD 27 Collection Method:					
RR#, Street Address, Box #: 1614-02 Phillips Bldg.					GPS unit (Make/Model: Garmin 60C)					
,				lle, OK 74004		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est, Accuracy: ☐ <3 m, ☑ 3-5 m, ☐ 5-15 m, ☐ >15 m				
Est. Accuracy:								] 3-13 III, [] > 13 III		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 23.5 ft.										
SECTION ROX: Depth(s) Groundwater Encountered (1)								(3) ft.		
N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							lay/yr			
Pump test data: Well water was ft. after hours pumping gpm										
W - NW NE - EST. YIELD										
WELL WATER TO BE USED AS:   Public water supply   Geothermal   Injection Well										
Sw SE Domestic Feedlot Oil field water supply Dewatering Other (specify below)										
Was a chemical/bacteriological sample submitted to Department? Yes No  If yes, mo/day/yr sample was submitted										
water well disinfected?   Yes   No										
5 TYPE OF CASING USED: Steel V PVC Other										
CASING JOINTS: Gland Clamped Welded Threaded										
Casing diameter 2 in to 8.5 ft. Diameter										
Casing height above land surface in., Weight										
TYPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel PVC Other (Specify)										
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)										
Continuous slot Willi slot Gauze wrapped Total cut Gher (specify)  Louvered shutter Key punched Wire wrapped Saw cut Gother (specify)  SCREEN-PERFORATED INTERVALS: From										
From T. 10 . T. 10 . T. 11, From 11, W 11.										
GRAVEL PACK INTERVALS: From										
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other										
Grout Intervals: From										
What is the nearest source of possible contamination:										
Septic tank							her (specify below)			
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well								•••••		
Direc	ction from well							LICONIC INTERVALC		
FROM	TO	LITHOLOG		FROM	TO LI	HO, LO	JG (cont.) or PL	UGGING INTERVALS		
0	23.5 Silt an	d Very Fine San	a w/Gypsum	-						
		1	ALL AND ALL AN							
				-		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
				_			31,44			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged										
under my invisdiction and was completed on (mo/day/year)										
Kansas Water Well Contractor's License No. 710 This Water Well Record was completed on (mo/day/year) ./ 1. 30										
INSTRUCTIONS: Use ty pewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.										
Z 1. 32 TES 1. 1.	winted to Kannon I	Jonar tment of Health	und Environment Bureau	of Water Geo	logy Section, 10	uuu sw ja	ekson St., Suite 420.	, 10pcka, Kansas 000 12-1507.		
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy										