WATE	R WELL	RECORD	Form W	WC-5	Di	vision of Water	Resources App. No). <u> </u>	
1 LOC	CATION OF	WATER WELL:	Fraction		Section	on Number	Township No.	Range Number	
	nty: Clark		SW 14 NE 14 SE	4 SE 14				R 24 □E 4₩	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:									
from nearest town or intersection: If at owner's address, check here . Latitude: .37.00.436 (in decimal degree Longitude: 0.99.56.485								(in decimal degrees)	
32 Ead 125 from Englewood					Eleva	Congitude: 039.30.400 (in decimal degrees)			
2 WATER WELL OWNER: 4/S Ranch					Collec	Collection Method:			
RR#, Street Address, Box #:					170	GPS unit (Make/Model: Garmin GPSmap60			
City, State, ZIP Code : Englewood, KS 67841					Digital Map/Photo, Topographic Map, Land Survey Est. Accuracy: S of m , 3-5 m, 5-15 m, >15 m				
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 100 ft.									
	H AN "X" IN TION BOX:								
	N WELL'S STATIC WATER LEVEL. 12								
	Pump test data: Well water was .12								
N	EST. YIELD. 50gpm. Well water was								
w	W E Bore Hole Diameter 8.3/4in. toft., andin. toft.								
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SV	SW X SE Domestic								
	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
S If yes, mo/day/yr sample was submitted									
l mile Water well disinfected? ☑ Yes ☐ No									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter 5 in. to									
Casing height above land surface. 24 in., Weight									
Steel Stainless Steel D PVC (ther (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)									
Louvered shutter Key punched Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 60 ft. to 100 ft., From ft. to ft.									
From									
GRAVEL PACK INTERVALS: From 20 ft. to 100 ft., From ft. to ft.									
From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
Grout Intervals: From .top. ft. to .20 ft., From ft. to ft., From ft. to ft., From ft.									
What is the nearest source of possible contamination: Septic tank									
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ✔ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well									
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well water well									
Direction from well .west Distance from well . 2500 feet									
FROM	TO	LITHOLOG	IC LOG	FROM	ТО	LITHO. LC	OG (cont.) or PLU	GGING INTERVALS	
0		nd		1			*************		
17		ack clay		 					
25	100 sa	nd and gravel		 					
				 					
		· · · · · · · · · · · · · · · · · · ·		 					
	 						that		
				1			· · · · · · · · · · · · · · · · · · ·		
				1			.,		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .10/27/2009 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 101 This Water Well Record was completed on (mo/day/year) 11/6/2009/									
under the business name of Bartel Well Drilling, Inc. by (signature) Mossilian by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies									
								answers. Send three copies Topeka, Kansas 66612-1367.	
Telephone	785-296-5522	. Send one copy to WAT						onstructed well. Visit us at	
http://www.kdheks.gov/waterwell/index.html. KSA 920 1212 Check: White Conv. Plus Conv. Plink Conv.									
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy									