pERMIT #T78-155

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)
Topeka, Kansas 66620

CWW Inv. #14990	Merkle #2-7			ТОР	sku, Kunsus 00020								
	Fraction 12 B		number	Township number	Range number								
Meade	M/4 NW 1/4 NW 1/4	7		т 35 S s	R 28W	E/W							
2. Distance and direction from nearest town or city: From South of Meade Lk go 12m. South Street address of well location if in city: m. South - lm. West - lm. South	1 - 4m East - 1 R.R. or	street:	222	ge Drilling Comp ! Sutton Place .chita. Kansas 6	_								
4. Locate with "X" in section below: Sk	etch map:			6. Bore hole dig9 in		9-5-78							
Forted Entry				Well depth 320 ft.									
NW NE	Ø			Hollow rod Jetted		I							
Portol Entry NW NE SW SE SW SW SW SE SW				8. Use: Domestic Public supply X Industry Irrigation Air conditioning Stock Lawn X Oil field water Other 9. Casing: Material Height: Above or below Threaded Welded Surface 28 in . RMP PVC X Weight 2.78 _ lbs./ft .									
							1 Mile	N X 8	T e	.	Dia. 5 in. to 320 ft. dep Dia. 5 in. to 320 ft. dep	th lagge No.	iches or 265
							5. Type and color of material		From	То	10. Screen: Manufacturer's	name	
							Surface		0	2	Sawed perf_ TypePVC		
Fine sand & medium to large sa	and & gravel	2	37	Slot/gauze	Length <u>80 *</u>								
	and a graver			ft.	and	ft.							
Blue clay		37	90	Gravel pack? Yes Size ro		-3/16 ./day/yr.							
Clay & fine sand, Blue, 80%san	nd	90	150	11. Static water level: 103 ft. below land su									
Brown clay		150	235	12. Pumping level below land									
Fine sand & medium to large sand		235	310	ft. after	hrs. pumping	_ g.p.m.							
				Estimated maximum yield — 13. Water sample submitted:		_g.p.m. ./day/yr.							
Sandy clay		310	320	·	Date	./ ddy/ yi /							
	 	<u> </u>		14. Well head completion: Pitless adapter	28 Inches above	arade							
		ļ											
				15. Well grouted? yes With: X Neat cement Bentonite Concrete Depth: From 0 ft. to 10 ft.									
				16. Nearest source of possibl	e contamination:								
				ft. 100 Direction NE Type oilwell Well disinfected upon completion? X Yes N									
		 		17. Pump:	X Not installed								
		ļ		Manufacturer's name Model number	HP Vo								
				Length of drop pipe									
				Type: Submersible	Turbin	e .							
(Use a second she	eet if needed)			Jet Centrifugal	Recipr Other	ocating S							
19 Flaustian 19 Pamerks			I	20. Water well contractor's		°							
Too read relig				This well was drilled under m		s report							
Topography:				Carlile Water W		118 💈							
Hill Slope				Business name Address BOX AA, Li		57901 \(\frac{1}{2}\)							
X Upland				Signed Scalinary	Minnapate	9-6-18							
Valley				Authorized rep	presentative	4							