

1 LOCATION OF WATER WELL: County: Meade		FRACTION: SW 1/4 SE 1/4		SECTION NUMBER: 8		TOWNSHIP NUMBER: T 35 S		RANGE NUMBER: R 29 E	
Distance and direction from nearest town or city street address of well if located within city? North on 23 from OK/KS line cross river bridge to 1st road going West 1/2 West 3/4 South into									
2 WATER WELL OWNER: Raydon Expl Co Inc 1-8 Wynona RR#, St. Address, Box # : 9400 N Broadway Ste 400 City, State, ZIP Code : Oklahoma City, Ok 73114 Board of Agriculture, Division of Water Resources Application Number: 20050101									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  N W E S			4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: Depth(s) Groundwater Encountered 1 27 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 4-3-05 Pump test data: Well water was 67 ft. after 1 hours pumping 20 gpm Est. Yield 20 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 6 in. to 40 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 24 in. weight 4.074 lbs./ft. Wall thickness or guage No. SDR 21.316 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 40 ft. to 80 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 80 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole plug Grout intervals: From 1 ft. to 24 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East How many feet? 1000									
LITHOLOGIC LOG FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 1 Surface 1 8 Sandy clay 8 19 Clay 19 52 Sand and gravel 52 80 Clay "blue"									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-3-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 4-3-05 under the business name of Howard Drilling Co Box 806 Beaver Ok 73932 by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.									