USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

CWW Inv. #13709 Adams 4-2	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
County 1250 FNL-1250 FWL	Section	number	Township number Range number
Meade $1/4 SE^{1/4} NW^{1/4}$		2	T 35S S R 29W E/W
2. Distance and direction from nearest town or city: \(\frac{1}{2} \) mi. 50. of port of entry on #23, turn Ea. 2 mi. to cattle R.R. or street: 500 Bitting Building			
Street address of well location if in city: guard -don't cross-turn So cross cattle grd City, state, zip code: Wichita, Kansas 67202 4. Locate with "X" in section below: Sketch map: go 4 mi. to another ctl. 6. Bore hole dia 2 in. Completion date 8/5/77			
4. Locate with "X" in section below: Sketch map: go 3 ml. to another ct. Regrdturn back right go 3 mi. Weno road			Well depth 260 ft.
then straight South 1 mi. to location.			7 Cable tool X_ Rotary Driven Dug
NWS NE PRESENTRY			Hollow rod Jetted Bored Reverse rotary
w E W			8. Use: Domestic Public supply X Industry
			Irrigation Air conditioning Stock Lawn Oil field water Other
sw se 2 2ms Ea. 1			9. Casing: Material Height: Above or below
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			Threaded Welded Surface 28 in.
s 1 Mile			RMPPVCXWeight_2.78_lbs./ft. Dia.5_in. to 150 ft. depth Wall Thickness: ipches or
5. Type and color of material	From	То	Dia. 5 in. to 260 ft. depth gage No. 265
	-		10. Screen: Manufacturer's name
Surface	0	2	Type PVC Dia 5"
Clay	2	20	Slot/gauze Length 80 t Set between 150 ft.
			ft. andft.
Sandy clay, Blue	20	40	Gravel pack? YES Size range of material 1/8-3/16
Clay	40-	60	11. Static water level: mo./day/yr95ft. below land surface Date8/5/77
Sandy clay	60	140	12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m.
Medium to large sand & sandy clay 60-40	140	160	ft. after hrs. pumping g.p.m.
Medium to large sand	160	180	Estimated maximum yield
Medium to large sand & sandy clay 80-20	180	200	Yes X No Date
medium to large sand & sandy clay 00-20			14. Well head completion: Pitless adapter
Medium to large sand & sandy clay 60-40	200	570	15. Well grouted? <u>Ves</u>
Medium to large sand & blue sandy clay 40-60	570	260	With: X Neat cement Bentonite Concrete Depth: From 0 ft. to 10 ft.
			16. Nearest source of possible contamination:
			ft. 100 Direction NE Type oilell
			Well disinfected upon completion? Yes No
			17. Pump: X Not installed
			Model number HP Volts
			Length of drop pipe ft. capacityg.p.m.
			Submersible Turbine
(Use a second sheet if needed)			Jet Reciprocating
(Use a second sneer it needed) 18. Elevation: 19. Remarks:	1		Centrifugal Other 6 20. Water well contractor's certification:
72.72			This well was drilled under my jurisdiction and this report
Topography: /M 2372			is true to the best of my knowledge and belief.
Hill 2377			Carlile Water Well Service 118 Business name Box 275, Liberal, KS No.
Slope ZZ7			Address Box 275, Liberal, KS 8/22/177
X Upland			Signed Ladward C. W Cana Date 0/23/11