


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Meade	SE 1/4 NW 1/4 SE 1/4	5	T 35 S	R 29 EW

Distance and direction from nearest town or city street address of well if located within city?

16 1/2 miles SE of Plains, KS

2 WATER WELL OWNER:	Hixon Development Co.	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Box 329	Application Number: 90 0177
City, State, ZIP Code :	Forgan, Okla. 73938	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 220 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 55 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 55 ft. below land surface measured on mo/day/yr 04-23-90 Pump test data: Well water was 70 ft. after 1 hours pumping 110 gpm Est. Yield 110 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 1/2 in. to 220 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 220 ft., Dia			Threaded
Casing height above land surface 24 in., weight			lbs./ft. Wall thickness or gauge No. 032
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 160 ft. to 220 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 120 ft. to 220 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other dirt
Grout Intervals: From 1 ft. to 20 ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? Northeast			How many feet? 75	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	18	Brown Clay			
18	28	Tan Sandy Clay			
28	32	Fine Sand			
32	58	Tan Clay			
58	65	Brown Clay			
65	74	Blue Clay			
74	93	Fine Sand			
93	105	Brown Clay			
105	126	Fine Sand			
126	152	Brown and Blue Clay			
152	188	Sand			
188	195	Brown Clay			
195	217	Sand			
217	220	Tan/White Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04-23-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 04-23-90 under the business name of Howard Drlg.Co. Box 806 Beaver, OK 73932 by (signature)
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.