		ATER WELL:	Fraction			tion Number			Range Number	
	Sumner		SW 1/4		2 1/4	2	T 35	S	R 3 E/W	
				address of well if locate	d within city	?				
109 N.	Arapaho	e St Caldwell	, Kansas							
2 WATE	R WELL O	WNER: Caldwell	l Farmers Co	op Grain Co.						
<del></del>		×# : P.O. Box		•			Board of Agricu	ture Divi	sion of Water Resources	
1 '		: Caldwel		122			Application Num	•	Sion of Viacor Foodardoo	
					21	A EIE\	<del></del>		1131	
WITH A	W'X" IN S									
		N L	Depth(s) Ground	water Encountered 1.		π	. 2	π.	3 ft.	
<b>↑</b>	1								yr1/1 <b>7</b> /96	
	1	.:-	•					-	mpinggpm	
	· NW	NE    <sub>E</sub>	Est. Yield \pmb N	🛦 gpm: Wellwater	was	ft. a	ıfter	hours pur	mpinggpm	
Wile W	İ	¦x	Bore Hole Diame	eter in. to	21		and	in	. to ft.	
₹ w F	$\overline{}$	<del>  *^•</del>   E \	WELL WATER	TO BE USED AS: 5	Public water	supply	8 Air conditioning	11	Injection well	
Ι. Ι	!		1 Domestic						Other (Specify below)	
	SW	SE	2 Irrigation							
	1								mo/day/yr sample was	
l <b>y</b> L	i		submitted	bacteriological campic	oubiliacu to		ater Well Disinfecte		No V	
- J 77/05 /	OF DI ANII	3	Capitillaca	= \A(\(\delta\) = \(\delta\)	0.0					
<u> </u>		CASING USED:		5 Wrought iron	8 Concr				di Clamped	
1 St		3 RMP (SR)	)	6 Asbestos-Cement		(specify belo	-		led	
(2 <b>)</b> P\		4 ABS		7 Fiberglass					aded <b>√</b>	
									. in. to ft.	
Casing hei	ight above l	and surface	. <b>6.24</b>	in., weight		lbs	ft. Wall thickness o	r gauge N	lo Sch. 40 ent	
TYPE OF	SCREEN C	R PERFORATION	MATERIAL		(7)PV	С	10 Asbe	estos-cem	ent	
1 St	teel	3 Stainless	steel	5 Fiberglass	8 RM	P (SR)	11 Othe	r (specify	)	
2 Br	rass	4 Galvanize	d steel	6 Concrete tile	9 AB		12 None	e used (or	en hole)	
		RATION OPENING		5 Gauze	d wrapped		8 Saw cut		11 None (open hole)	
	ontinuous s				rapped		9 Drilled holes		The traction (open tricity)	
	ouvered shi			7 Torch	• •					
i						A C			to	
SCREEN	PERFURA	ED INTERVALS:	From			IL., F1	OIII	٠٠٠٠١١.	to	
_ ا	2DA)/EL DA	OK INTERMALO							to	
ا ا	SKAVEL PA	CK INTERVALS:								
									to	
6 GROUT	T MATERIA	L: 1 Neato	ement :	2 Cement grout	3 Bento	nite 4	Other			
Grout Inter	rvals: Fro	m <u>0</u>	ft. to 7	ft., From	7 ft. :	to 9.	ft, From			
1		ource of possible					stock pens		bandoned water well	
1 Sept	tic tank	4 Latera	al lines	7 Pit privy		11 Fue	l storage	15 C	il well/Gas well	
			•			12 Fert	12 Fertilizer storage (16) Other (specify below)			
								ormer UST Basin		
Direction 1	_	NE	-9- P	2 1 00ayuru			ny feet? 165			
FROM	TO	1112	LITHOLOGIC	LOG	FROM	TO		JGGING II	VITERVALS	
0	1	Clay, Medium								
1	2	Clay, Light Re		77.44		<b></b>			V = = 7 +0 -0.1	
					<del> </del>	<del> </del>	·			
2	4	Silt, Medium l								
4	5	Silt, Light Red				ļ				
5	10	Clay, Light Re								
10	14	Sand, Light Yo	ellow Brown							
14	20.5	Sand, Light Yo	ellow Brown							
20.5	21	Shale, Light B							-	
						<b></b>				
				- m						
							MW5 , Tag # 001468			
							Project Name: Cald			
							GeoCore # 180 , KD	HE # U2 0	96 1316	
7 CONTR	PACTOPS		S CERTIFICATI	ON: This water well wa	(1) constru	ucted (2) re	constructed or (3)	olugaed i ii	nder my jurisdiction	
L COMIK	violoko (		O OERHIFIOAH	1/10/06						
and was c	ompleted o	n (mo/day/year) .		527 -··					y knowledge and belief. 1/30/96	
l .		Contractor's Licens			vvater vvell		s completed on (mo/	uay/yr) .	0.01	
***************************************	business n			e Services, Inc.		by (sign	·	· u	1	
INSTRI Depart	UCTIONS: Us ment of Health	e typewriter or ball poir and Environment, Bure	nt pen. <u>PLEASE PR</u> eau of Water, Topek	<u>RESS FIRMLY</u> and <u>PRINT</u> cle a, Kansas 66620-0001.  Tele	early. Please fill phone: 913-296-	l in blanks, und -5545. Send or	erline or circle the correcte to WATER WELL OW	t answers. 3 NER and ret	Send top three copies to Kansas ain one for your records.	