

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Sumner</u>	SE 1/4 SW 1/4 NE 1/4	2	T 35 S	R 3 EW

Distance and direction from nearest town or city street address of well if located within city?

24 East Central, Caldwell, Kansas MMW11

2 WATER WELL OWNER:	RR#, St. Address, Box # :	City, State, ZIP Code :	Board of Agriculture, Division of Water Resources
<u>Jim Mitchell</u>	<u>525 S.A. Street</u>	<u>Arkansas City, KS. 67022</u>	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>26</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>24</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>24.32</u> ft. below land surface measured on mo/day/yr <u>10-26-92</u>
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter <u>7.5/8</u> in. to <u>26</u> ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded X
Blank casing diameter 2 in. to 16 ft., Dia.			
Casing height above land surface 0 in., weight lbs./ft.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS:	From 16 ft. to 26 ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From 14 ft. to 26 ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 1 ft.	From 1 ft. to 14 ft.	From ft. to ft.	
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? <u>East</u>				How many feet? <u>130</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Clay, dark brown			
2	12	Clay, reddish brown			Flush mount cover
12	14	Sandy clay, reddish brown			Site ID # 00090560
14	17	Sand, reddish brown, fine to coarse			
17	22	Clay, reddish brown			
22	26	Sand and gravel with clay stringers			
		dark reddish brown			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>09-11-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>527</u> This Water Well Record was completed on (mo/day/yr) <u>11-06-92</u> under the business name of <u>GeoCore Services, Inc.</u> by (signature) <u>Doug Ray</u>
