

CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction ( 1/4 1/4 1/4) Section-Township-Range changed:

listed as 4-35<sub>s</sub>-32<sub>w</sub>

changed to SW-NW-NE 4-35<sub>s</sub>-32<sub>w</sub>

Other changes: Initial statements: \_\_\_\_\_

Changed to: \_\_\_\_\_

Comments: \_\_\_\_\_

verification method: Hayne 7.5; disc on form

initials: SD date: 5/4/97

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726  
to: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction 1/4 1/4 1/4 Section Number 4 Township Number T 35 S Range Number R 32 W  
 COUNTY: *Sevier*

Distance and direction from nearest town or city street address of well if located within city?  
 FROM LIBERAL, KS. - 7 MILES EAST ON BLUE-BELL ROAD

2 WATER WELL OWNER: NABARRO, OSCAR & VICTOR and *Catarino Hernandez*  
 R.R., St. Address, Box #: R.R. 12 -- BOX 341 Board of Agriculture, Division of Water Resources  
 City, State, ZIP code: LIBERAL, KS 67901- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1	NW	X	NE	2	SW	SE	3	4	5
W				E					
6	7	8	9	10	11	12	13	14	15

4 DEPTH OF COMPLETED WELL 255 ELEVATION: 0  
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.  
 WELL'S STATIC WATER LEVEL 200 ft. below land surface measured on no/day/yr 04/29/94  
 Pump testdata: Well water was 0 ft. after 0 hours pumping 0 gpm  
 Estimated Yield 35 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm  
 Bore Hole Diameter 9 in. to 255 ft., and in. to 0 ft.  
 WELL WATER TO BE USED AS: DOMESTIC  
 Was a chemical/bacteriological sample submitted to department? No ;  
 If yes, no/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED  
 Blank casing diameter 5 in. to 255 ft., Dia in. to 0 ft., Dia in. to 0 ft.  
 Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21  
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC  
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 220 ft. to 250 ft., From 0 ft. to 0 ft.  
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.  
 GRAVEL PACK INTERVALS: From 40 ft. to 255 ft., From 0 ft. to 0 ft.  
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE  
 Grout intervals: From 0 ft. to 40 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.  
 What is the nearest source of possible contamination: WATERTIGHT SEW.  
 Direction from well? NORTHWEST How many feet? 140

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	22	TOPSOIL FINE SAND SANDY CLAY			
22	40	BROWN CLAY			
40	55	CALACHIE CLAY			
55	120	CALACHIE CLAY RED CLAY			
120	140	SANDY CLAY			
140	230	MEDIUM SAND			
230	235	CLAY			
235	255	MEDIUM SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (no/day/year) 05/03/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (no/day/yr) 11/02/94 under the business name of JOE'S WELL SERVICE, INC. by (signature) *Joseid Cust*