USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number		Township number	Range number	
1. Location of well:	Seward	Center NE 1/4 S	W _{1/4}	14	-	r 35 s	_R 34	₽
	ction from nearest town or city:	of m.	ı			Fuller		
3 west Liberal South side of rd. Street oddress of well location if in city:					street: RR 1 ate, zip code: Liberal, Kansas 67901			
4. Locate with "X" i	in section below:	Sketch map:	City, si	die, zip	code: 111	6. Bore hole dia. 9 in.		25/81
4. Locale will X		skerch map:				Well depth260 ft.		
						7 Cable tool X_ Rotary Driven Dug		
E SW SE						Bored Reverse rotary 8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn X Oil field water Other 9. Casing: Material PVC Height: Above or below Threaded Welded Surface 14 in.		
<u> </u>						Threaded Welded RMP PVC clue		in. _lbs./ft.
1 1 M				.		PVC glue Dia. 5 in. to 28 ft. dep	th!Wall Thickness: inc	hes or
5. Type and color of	material			From	То	Dia in. to ft. dept	h gage No. OZ JO	==
					100	10. Peer Manufacturer's n		
Overburden				0	100	Type PVC Slot/gauze 1/16	_ Dia	
Fine sand & clay				100	180	Set between180	ft. and <u>260</u>	f1.
Medium sand & clay				180	200	ft. a	nd	ft.
Neuram sand a cray						Gravel pack? Yes_ Size rail 11. Static water level:		/day/yr.
Medium to coarse sand & clay				200	250	_100 _ft. below land sur		
Clay				250	260	12. Pumping level below land	surfaces:	
					ft. after hrs. pumping g.p.m ft. after hrs. pumping g.p.m.			
				<u> </u>	<u> </u>	Estimated maximum yield		
					13. Water sample submitted: mo./day/yr. Yes X No Date 14. Well head completion: Pitless adapter 14 Inches above grade 15. Well grouted? Yes With: X Neat cement Bentonite Concrete Depth: From 3 ft. to 13 ft. 16. Nearest source of possible contamination: None ft. Direction Yes No			
								-
				-	+	17. Pump:	Not installed	
						Manufacturer's RIMBOULDS 5 Model number 210 HP 5 40 lts Length of drop pipe 210 ft. capacity 60 g.p.m.		
				 	†	Type:		
						X Submersible	Turbine Recipro	
	(Use a second	sheet if needed)				Jet Centrifugal	Recipro	Sec
18. Elevation: 19. Remarks:						20. Water well contractor's		
Well drilled in field no source of contamination.						This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Topography: 17. Pumped for 10 days-pulled pump-capped						T&W Water Well Service 142		
						Business name		ense No.
X Upland						Address Box B16 11	Q.	6/1/81
Valley						Authorized rep	presentative Date	