		WATER	R WELL RECORD	orm WWC-5	KSA 82a	-1212		
LOCATION OF WA		Fraction			tion Number	Township Nur		Range Number
ounty: Sewa		<u> </u>	SW 14 SL Idress of well if located	<u> </u>	17	T 35	S	R 34 E/W
			al, Ks 6					
WATER WELL OW	NER: Lloyd	Ogler	Flynn Energ					
R#, St. Address, Bo			RHI	<b>A</b> 14		Board of Ag	riculture, D	Division of Water Resources
ty, State, ZIP Code	: Liber	ral	HANN essey,	W. 7:	3742	Application	Number:	T85-18
LOCATE WELL'S L AN "X" IN SECTIO	OCATION WITH N BOX:	4 DEPTH OF CO	OMPLETED WELL	125	ft. ELEVA	TION:	# 2	
<u></u>	<del>`                                    </del>	WELL'S STATIC	WATER LEVEL . 9.5	۲۰ ۲۰ ۲۰ ۲۰ ۲۰ د د	olow lond our	face measured on	11. 3.	1/12/25
ii								mping <b>5.5</b> . gpm
NW	NE							
!	!	Est. Yield / (	. gpm: Well water	was	π.a Λ	tter	hours pur	nping gpm
w	E	i .						to
1 :		1		5 Public water		8 Air conditioning		
sw	SE	1 Domestic						Other (Specify below)
	Ī	2 Irrigation		_	-			
<b>X</b> 1		Was a chemical/b	acteriological sample si	ubmitted to De	•	•	-	mo/day/yr sample was sub-
	<u> </u>	mitted			Wa	ter Well Disinfected	? Yes 🕽	<b>∠</b> No
TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Concre	ete tile	CASING JOIN	ITS: Glued	. 🗶 Clamped
1 Steel	3 RMP (S	R)	6 Asbestos-Cement	9 Other	(specify below	v)	Welde	ed
2 PVC	4 ABS		7 Fiberglass					ded
ank casing diameter	·	.in. to /.Q.C	7 ft., Dia	in. to		ft., Dia	i	n. to <u></u> ft.
asing height above !	and surface	14	in., weight	200	Ibs./	ft. Wall thickness or	gauge No	0.265
YPE OF SCREEN C	R PERFORATIO	N MATERIAL:		<u>7 PV</u>	C_	10 Asbe	stos-ceme	nt
1 Steel	3 Stainless	s steel	5 Fiberglass		IP (SR)	11 Other	r (specify)	<i></i>
2 Brass	4 Galvaniz	zed steel	6 Concrete tile	9 AB	, ,		used (ope	
CREEN OR PERFO				d wrapped		8 Saw cut	(	11 None (open hole)
1 Continuous sk		fill slot		rapped		9 Drilled holes		Tritono (oponinoio)
2 Louvered shut		ey punched	7 Torch	• •				
CREEN-PERFORAT		From 9.	5 # 15	~ 280	# Ero	~		>
ONELIN-FEM ONAT	ED INTERIVALS.							
ODAVEL DA	OK INTERVALO	From	π. το	280	π., Fro	m	π. το	o
GHAVEL PA	CK INTERVALS:							
CDC/F MATERIA		From	ft. to			m		
GROUT MATERIA			2 Cement grout					
			ft., From	π.				. ft. to
hat is the nearest s	•							pandoned water well
· · · · · · · · · · · · · · · · · · ·	4 Later	ral lines	7 Pit privy		11 Fuel	storage		
2 Sewer lines	5 Cess	•	8 Sewage lago	on	12 Fertil	zer storage	16 O	ther (specify below)
3 Watertight sev	ver lines 6 Seep	page pit	9 Feedyard		13 Insec	ticide storage		
irection from well?	East				How ma			
FROM TO		LITHOLOGIC L	LOG	FROM	то	L	ITHOLOG	IC LOG
0 95	Over	burden						
15 180	Clay							
80 200	Fine	Sand Strea	ks & clay					
200 260	med	Send + cl						
260 280		Sand to	<b>A</b>					
	7							
	·				<del>                                     </del>			
					<b></b>			
	<b> </b>							
	L		VI.		L			
CONTRACTOR'S	OR LANDOWNE	R'S CERTIFICATION	ON: This water well wa	ıs (1) constru	cted, (2) reco	enstructed, or (3) pl	ugged und	ler my jurisdiction and was
empleted on (mo/day	11. 11	P.5						owledge and belief. Kansas
ater Well Contractor	• •	142	This Water W				1/1/1/2	
ider the business na	~	A 1 . 1 . 1	Sorvice	WE	by (signa	~ ~ 1 1 / /	12 -	114
				PRINT clear			circle the	e correct answers. Send top
ree copies to Kansas	Department of He	ealth and Environm	ent, Division of Environ	ment, Environ	mental Geolo	gy Section, Topeka.	KS 66620.	Send one to WATER WELL
WNER and retain o	ne for your record	ds.						