

1 LOCATION OF WATER WELL: County: Stevens		Fraction C 1/4 NE 1/4 NE 1/4		Section Number 16		Township Number T 35 S		Range Number R 35		E/W	
Distance and direction from nearest town or city street address of well if located within city? N. of Hooker to State Line 1N., 4.7E., & S into											
2 WATER WELL OWNER: Texaco Inc. RR#, St. Address, Box # : P.O. Box 2700 City, State, ZIP Code : Pampa, Tx 79066-2700						#3 Wray TF Board of Agriculture, Division of Water Resources Application Number: 970040					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 				4 DEPTH OF COMPLETED WELL: 365 ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1. 130 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ... 130 ft. below land surface measured on mo/day/yr ... 1-6-97 Pump test data: Well water was ... 200 ft. after ... 1 hours pumping ... 95 gpm Est. Yield ... 95 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter ... 9 1/4 in. to ... 365 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter ... 5 in. to ... 365 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface ... 24 in., weight ... 2.902 lbs./ft. Wall thickness or gauge No.280 SDR 21 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ... 280 ft. to ... 360 ft., From ft. to ft. GRAVEL PACK INTERVALS: From ... 185 ft. to ... 360 ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole Plug Grout intervals: From ... 0 ft. to ... 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Northwest How many feet? 150 FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 6 Surface 6 27 Clay 27 192 Sandy Clay / Clay 192 365 Sand											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... 1-6-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWCL - 430 This Water Well Record was completed on (mo/day/yr) ... 1-6-97 under the business name of Howard Drlg. Box 806 Beaver, ok 73932 by (signature) <i>Howard Drlg.</i>											
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.											