WATER WELL R				sion of Water urces App. N	1	Well ID	
Original Record 1 LOCATION QF #W		tion,		tion Number			
County:		1/1 /W/45W/45	W/4	6	TPS	R 3 S □ E > W	
2 WELL OWNER: L		By redove S	treet or Rur	al Address v	where well is located	(if unknown, distance and	
		d	irection from r	nearest town or	intersection): If at owne	r's address, check here:	
Address:			J	C 1	1 6,000	F 11/ 1	
Address: Huco	on State: KS ZIP	67951	9 M. lx	's rout	41 4 10 FULL	es East-Allego Von	
3 LOCATE WELL							
WITH "X" IN	4 DEPTH OF COMPLE	TED WELL:	₹ .7 ft.	5 Latitu		(decimal degrees)	
SECTION BOX:	Depth(s) Groundwater Encou					(decimal degrees)	
N	2) ft. 3)				: □ WGS 84 □ NA		
	WELL'S STATIC WATER I				for Latitude/Longitude		
	below land surface, measured on (mo-day-yr) above land surface, measured on (mo-day-yr)						
NW NE	Pump test data: Well water was			☐ Land Survey ☐ Topographic Map			
w E	after hours pump	oingg	pm				
SW SE	1	vas ft.					
X SW SE	after hours pump		pm	6 Elevai	ion. fl	. Ground Level TOC	
S	Estimated Yield:50	m Žin to	ft and			GPS Topographic Map	
mile	,	in. to	_				
7 WELL WATER TO							
1. Domestic:	5. □ Public Water Su	pply: well ID		10. 🗌 Oil	Field Water Supply: 1	ease	
Household	6. Dewatering: ho	w many wells?			lole: well ID		
Lawn & Garden	 7. Aquifer Recharg 	ge: well ID			sed Uncased		
☐ Livestock	8. Monitoring: we				ermal: how many bore		
2. Irrigation	9. Environmental Rem				osed Loop		
3. ☐ Feedlot 4. ☐ Industrial	☐ Air Sparge ☐ Recovery	☐ Soil Vapor Ex ☐ Injection	uraction			ischarge Inj. of Water	
			137				
	iological sample submitted	to KDHE? Y	es 🔼 No	If yes, date	sample was submitte	ed:	
Water well disinfected?	HEED CALL STRUCK	Other	CACIN	IC IONITE	McClared Clamas	d D Walded D Threaded	
8 TIPE OF CASING	OSED: Diegi ALLAC D	Other	CASII	10 JOHN 1 3.	Clampe	d □ welded □ Infeaded	
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: A Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft., Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No.							
Casing diameter	in. to57 ft., Dian	neterii Weight	n. to lbs./ft.	ft., Diam Wall thick	eterin. to	200 ft.	
Casing height above land	surface	Weight	n. to lbs./ft.	ft., Diam Wall thick	eterin. to ness or gauge No.	2.00ft.	
Casing height above land a TYPE OF SCREEN OF	surface	Weight AL:	n. to lbs./ft.	Wall thick	ness or gauge No	1.20	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv	turface	Weight AL: ▼PVC	lbs./ft.	Wall thick	ness or gauge No	2.00 ft.	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv	surface	WeightAL: Mary PVC le □ None use	lbs./ft.	Wall thick ☐ Oth	er (Specify)		
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	WeightAL: AL: YPVC Ie □ None use	lbs./ft. ed (open hole ch Cut	Wall thick ☐ Oth :) rilled Holes	er (Specify)		
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	WeightAL:	lbs./ft. ed (open hole ch Cut	Wall thick Oth Constitute Holes	er (Specify)	1.00	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	WeightAL:	lbs./ft. ed (open hole ch Cut	Wall thick Oth Constitute Holes	er (Specify)	1.00	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE	surface	Weight	cd (open hole ch Cut D Cut N . ft., From	Wall thick Oth Tilled Holes Tone (Open Ho	Other (Specify)	ft. to ft ft.	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG	surface	Weight	cd (open hole ch Cut D Cut N . ft., From ft., From tonite D	Wall thick Oth Tilled Holes Tone (Open Holes The first to	Other (Specify)	ft. to ft ft ft.	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAG GROUT MATERIA Grout Intervals: From	surface	Weight	cd (open hole ch Cut D Cut N . ft., From ft., From tonite D	Wall thick Oth Tilled Holes Tone (Open Holes The first to	Other (Specify)	ft. to ft ft ft.	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl	surface	Weight	ed (open hole ch Cut	Wall thick Other rilled Holes one (Open Homes fi. to fi. to ther	or (Specify)	fl. to ft f	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines	aurface	Weight	cd (open hole ch Cut D Cut N . ft., From ft., From tonite O . to .	Wall thick Other rilled Holes one (Open Holes ft. to ther	cr (Specify)	ft. to ft.	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lire	aurface	Weight	cd (open hole ch Cut D Cut N . ft., From ft., From tonite O . to .	Wall thick Other rilled Holes one (Open Holes fi. to fi. to ther	cr (Specify)	ft. to ft	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify)	aurface	Weight	cd (open hole ch Cut	Wall thick Oth Tilled Holes Tone (Open Ho The too Th	Other (Specify)	fl. to fl fl fl. off. to fl fl.	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well?	aurface	Weight	cd (open hole ch Cut	Wall thick Other rilled Holes one (Open Homes for the following files to the file	r (Specify)	fl. to fl ft ft.	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well?	Jurface	Weight	cd (open hole ch Cut	Wall thick Oth Tilled Holes One (Open Home first to the first to th	or (Specify)	ft. to ft ft. to ft ft. to ft ft. cide Storage oned Water Well ell/Gas Well pLUGGING INTERVALS	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lire Other (Specify) Direction from well? 10 FROM TO	aurface	Weight	ch (open hole ch Cut	Wall thick Oth rilled Holes fone (Open Home filled to the filled to th	or (Specify)	fl. to fl ft ft.	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAG GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lir Other (Specify) Direction from well? 10 FROM TO	Jurface	Weight	ch Cut D Cut N ft., From tonite D con D FROM FROM 740	Wall thick Other rilled Holes fone (Open Home first to the first f	or (Specify)	ft. to ft ft. to ft ft. cide Storage oned Water Well cll/Gas Well rPLUGGING INTERVALS www. www. stands.	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Seyer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 7 20 10 TYPE OF SCREEN OF STAIN TO TYPE OF STAIN TO	purface	Weight	ch Cut D Cut N ft., From tonite D con D FROM FROM THE	Wall thick Oth rilled Holes fone (Open Home of the continuous filter) ther	or (Specify)	ft. to ft ft. to ft ft. to ft ft. cide Storage oned Water Well cll/Gas Well r PLUGGING INTERVALS L Cay Say Say	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 7 7 7 7 7 7 7 7 7 7 7 7 7	Jurface	Weight	Ibs./ft. ed (open hole ch Cut	Wall thick Oth Tilled Holes Tone (Open Home first to the first f	or (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. cide Storage oned Water Well bll/Gas Well r PLUGGING INTERVALS r LANGE Sand Streat say Clay Sand Red Clay Luyer Sand Red Clay Luyer	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Seyer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO TO TO TO TO TO TO TO TO TO TO TO TO	James In Section In Se	Weight	ch Cut D Cut N ft., From tonite D con D FROM FROM THE	Wall thick Oth rilled Holes fone (Open Home of the continuous filter) ther	or (Specify)	ft. to ft ft. to ft ft. to ft ft. cide Storage oned Water Well cll/Gas Well r PLUGGING INTERVALS L Cay Say Say	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lir Other (Specify) Direction from well? 10 FROM TO 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	James In Section In Se	Weight	Ibs./ft. ed (open hole ch Cut	Wall thick Oth Tilled Holes Tone (Open Home first to the first f	or (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. cide Storage oned Water Well bll/Gas Well r PLUGGING INTERVALS r LANGE Sand Streat say Clay Sand Red Clay Luyer Sand Red Clay Luyer	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lir Other (Specify) Direction from well? 10 FROM TO 7 20 130 130 130 130 130 130 130 130 130 13	Jurface	Weight	Ibs./ft. ed (open hole ch Cut	Wall thick Oth Tilled Holes Tone (Open Home first to the first f	or (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. cide Storage oned Water Well bll/Gas Well r PLUGGING INTERVALS r LANGE Sand Streat say Clay Sand Red Clay Luyer Sand Red Clay Luyer	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG G	Jurface	Weight	Ibs./ft. ed (open hole ch Cut	Wall thick Oth Tilled Holes Tone (Open Home first to the first f	or (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. cide Storage oned Water Well bll/Gas Well r PLUGGING INTERVALS r LANGE Sand Streat say Clay Sand Red Clay Luyer Sand Red Clay Luyer	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Seyer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 7 7 7 7 7 7 7 7 7 7 7 7 7	Jurface	Weight	Ibs./ft. ed (open hole ch Cut	Wall thick Oth rilled Holes one (Open Home of the tother	other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. cide Storage oned Water Well cll/Gas Well r PLUGGING INTERVALS r LANGE Sand Strats gundal Res Clay buyer onstructed, or I plugged	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lir Other (Specify) Direction from well? 10 FROM TO 7 20 40 40 40 40 70 170 710 710 71	Jurface	Weight	Ibs./ft. ed (open hole ch Cut	Wall thick Oth rilled Holes fone (Open Home first to the first to first	constructed, reconstructed, reconstr	ft. to	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG G	James In Section In Se	Weight	Ibs./ft. ed (open hole ch Cut	Wall thick Other rilled Holes fone (Open Homes one) The first to th	other (Specify)	fl. to	
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 7 7 7 7 7 7 7 7 7 7 7 7 7	Jurface	Weight	Ibs./ft. ed (open hole ch Cut	Wall thick Oth rilled Holes fone (Open Home of the first to the firs	oness or gauge No	fl. to	

KSA 82a-1212

Revised 9/10/2012

Visit us at http://www.kdheks.gov/waterwell/index.html