

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Stevens		1/4 C-NE 1/4 NE 1/4	10	T 35 S	R 35 E/W
Distance and direction from nearest town or city street address of well if located within city? From Liberal, go west on 2nd street road then 4mi on west on dirt road and south to location.					
2 WATER WELL OWNER: William DeCamp Oil Company Mid-Western Exploration					
RR#, St. Address, Box #: Box D Board of Agriculture, Division of Water Resources					
City, State, ZIP Code: Tyrone, Oklahoma 73951 Application Number: T 82-275					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 300 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 176 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 124 ft. below land surface measured on mo/day/yr 5/22/82			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 60 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 300 ft., and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot <u>6 Oil field water supply</u> 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> ; If yes, mo/day/yr sample was submitted					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: <u>Glued</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded					
Blank casing diameter 5 in. to 220 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface 28 in., weight 2.78 lbs./ft. Wall thickness or gauge No. 256					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 220 ft. to 300 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 120 ft. to 300 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? Northeast of water well. How many feet? 100'					
FROM TO LITHOLOGIC LOG			FROM TO LITHOLOGIC LOG		
0	2	surface			
2	93	sandy clay			
93	106	clay			
106	141	sandy clay			
141	183	clay			
183	211	caliche			
211	220	gravel			
220	300	clay & fine sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 22, 1982 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) June 1, 1982					
under the business name of Carlile Water Well Service, Inc. by (signature) <i>Edward E. Means</i>					
INSTRUCTIONS: Use typewriter or ball point pen, <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

35

E/W

SEC.

10

1/4

NE 1/4

NE 1/4

NE 1/4