

1 LOCATION OF WATER WELL: County: STEVENS		Fraction NW 1/4 NW 1/4 SW 1/4	Section Number 10	Township Number T 35 S	Range Number R 36 E/W
Distance and direction from nearest town or city street address of well if located within city? FROM HUGOTON SEVEN (7) MILES EAST, TEN & ONE-HALF (10 1/2) MILES SOUTH & ONE (1) MILE WEST.					
2 WATER WELL OWNER: DOUGLAS MILLS RR#, St. Address, Box #: RT. 1, BOX 72A City, State, ZIP Code: HUGOTON, KS 67951 Board of Agriculture, Division of Water Resources Application Number: 41,679					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div><div>1 Mile</div><div><div>N</div><div>W</div><div>E</div><div>S</div><div><div>NW</div><div>NE</div><div>SW</div><div>SE</div><div>X</div></div></div></div>		4 DEPTH OF COMPLETED WELL: 620 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 186 ft. below land surface measured on mo/day/yr 8/23/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 26 in. to 620 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter XX 16 in. to 620 in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 42.5 lbs./ft. Wall thickness or gauge No. 250 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From SCREEN 420 ft. to 460 ft., From PERF. 460 ft. to 580 ft. From SCREEN 580 ft. to 620 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 620 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) CROP LAND, NOTHING IMMEDIATE VICINITY Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS	
0	200	SURFACE, SAND & CLAY			
200	260	FINE TO MED. SAND			
260	360	FINE SAND			
360	400	BLUE & BROWN CLAY W/FINE SAND			
400	600	FINE TO MED. SNAD			
600	616	MED. TO COARSE SAND			
616	640	RED CLAY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/23/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 225 This Water Well Record was completed on (mo/day/yr) 9/15/95 under the business name of KTM DRILLING, INC. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					