

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: STEVENS	SW 1/4 SW 1/4 NE 1/4	6	T 35 S	R 36 E/W

Distance and direction from nearest town or city street address of well if located within city?

FROM HUGOTON 9 MILES SOUTH, 4 1/2 MILES EAST & 1/2 MILE SOUTH.

2 WATER WELL OWNER: JIM GOOCH	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 214 E. 2ND STREET	Application Number: 42,523
City, State, ZIP Code: HUGOTON, KS 67951	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 675 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 160 ft. below land surface measured on mo/day/yr 6/16/97 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 26 in. to 675 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded X
2 PVC 4 ABS	7 Fiberglass		Threaded
Blank casing diameter 16 in. to 675 ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface 12 in., weight 42.5 lbs./ft. Wall thickness or gauge No. 250			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel 3 Stainless steel	8 RMP (SR)	11 Other (specify)	
2 Brass 4 Galvanized steel	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot 3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter 4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From SCREEN 270 ft. to 290 ft., From PERF. 290 ft. to 575 ft.			
From SCREEN 575 ft. to 675 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 675 ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
CROPLAND-NOTHING
IMMEDIATE VICINITY

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	200	SURFACE, SAND & CLAY			
200	240	SANDY BROWN CLAY W/FINE SAND			
240	300	FINE TO MED. SAND			
300	500	BLUE & YELLOW CLAY W/FINE SAND			
500	664	FINE TO MED. SAND			
664	680	RED CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/16/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 225 This Water Well Record was completed on (mo/day/yr) 6/26/97 under the business name of KTM DRILLING, INC. by (signature) <i>Donald W. Smith</i>
