

1 LOCATION OF WATER WELL: County: Stevens	Fraction NE 1/4 NW 1/4 NW 1/4	Section Number 14	Township Number T 35 S	Range Number R 36 E
---	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

16 miles West 2 South 1/4 East and South 100' into from Liberal, KS

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Arden Webb RFD 1 Hugoton, KS 67951	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 280 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 170 ft. 2. . ft. 3. . ft. WELL'S STATIC WATER LEVEL 110 ft. below land surface measured on mo/day/yr 9-28-89 Pump test data: Well water was 122 ft. after 2 hours pumping 20 gpm Est. Yield 17 gpm: Well water was . ft. after . hours pumping . gpm Bore Hole Diameter 9 in. to 280 ft., and . in. to . ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped .
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 240 ft., Dia . in. to . ft., Dia . in. to . ft.			11 Other (specify) .
Casing height above land surface 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0-265			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
1 Steel	3 Stainless steel	9 ABS	11 Other (specify) .
2 Brass	4 Galvanized steel		12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	9 Drilled holes	
2 Louvered shutter	4 Key punched	10 Other (specify) .	
SCREEN-PERFORATED INTERVALS: From . 240 ft. to 280 ft., From . ft. to . ft., From . ft. to . ft.			
GRAVEL PACK INTERVALS: From 100 ft. to 280 ft., From . ft. to . ft., From . ft. to . ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other .
Grout Intervals: From 0 ft. to 20 ft., From . ft. to . ft., From . ft. to . ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? West		How many feet? 275		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	110	Overburden			
110	140	Fine sand and clay			
140	160	Fine sand and clay			
160	180	Fine sand and clay			
180	200	Medium sand			
200	220	Medium sand			
220	240	Medium sand			
240	260	Medium sand and clay			
260	280	Medium sand and clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-28-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 9-28-89 under the business name of T & W Water Well Service, Inc. by (signature) <i>[Signature]</i>
