

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: STEVENS		NE 1/4 NE 1/4 NE 1/4	15	T 35 S	R 36 E/W
Distance and direction from nearest town or city street address of well if located within city? 8 miles East & 11 miles South of Hugoton					
2 WATER WELL OWNER: DWAIN TOWNER					
RR#, St. Address, Box # : RR 1, Box 60A			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : HUGOTON, KS 67951			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 622 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 127 ft. below land surface measured on mo/day/yr 8-17-84			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 26 in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No. X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded . X
			7 Fiberglass		Threaded
Blank casing diameter 16 in. to 622 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 42.5 lbs./ft. Wall thickness or gauge No. 25					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 280 ft. to 622 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 622 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	Cropland-nothing
Direction from well?		How many feet?		immediate vicinity	
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	180	Surface			
180	300	Sand clay w/brown clay & fine sand			
300	420	Fine sand & clay			
420	500	Fine sand & clay w/med coarse sand			
500	570	Blue clay sticky			
570	640	Med coarse sand & gravel			
640	650	Red clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-16-84 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 225 This Water Well Record was completed on (mo/day/yr) 8-24-84					
under the business name of KTM DRILLING, INC.					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					