

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: STEVENS	C $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$	11	T 35S S	R 36W E W

Distance and direction from nearest town or city street address of well if located within city?

10 MILES SOUTHWEST WOODS, KS

2 WATER WELL OWNER: BEREDCO DRILLING	#1-11 CASEBEER
RR#, St. Address, Box #: 401 E DOUGLAS, # 402	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: WICHITA, KS 67202	Application Number: 940488

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 360 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 140 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 140 ft. below land surface measured on mo/day/yr 12-9-94 Pump test data: Well water was 160 ft. after 1 hours pumping 130 gpm Est. Yield 130 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to 360 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 6 in. to 360 ft. Dia			
Casing height above land surface 24 in. weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR 21			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	6 Concrete tile	8 RMP (SR)	11 Other (specify)
3 Stainless steel		9 ABS	12 None used (open hole)
4 Galvanized steel			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS:	From 260 ft. to 360 ft.		
GRAVEL PACK INTERVALS:	From 240 ft. to 360 ft.		

6 GROUT MATERIAL:	1 Heat cement	2 Cement grout	3 Bentonite	4 Other HOLE PLUG
Grout intervals: From 1 ft. to 20 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? East			13 Insecticide storage	
			How many feet? 125	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL	242	250	SANDY CLAY
2	6	CLAY	250	259	SAND
6	43	SANDY CLAY	259	263	CLAY
43	54	SAND	263	296	SAND
54	64	SANDY CLAY	296	306	CLAY
64	78	SAND	306	311	SAND
78	91	CLAY	311	318	CLAY
91	100	SAND	318	343	SANDY CLAY
100	115	CLAY	343	356	SAND
115	137	SANDY CLAY	356	360	CLAY
137	148	CLAY			
148	158	SANDY CLAY			
158	168	CLAY			
168	207	SANDY CLAY			
207	242	SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-9-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWCL-430 This Water Well Record was completed on (mo/day/yr) 12-9-94 under the business name of HOWARD, DRILG. CO. BOX 806 BEAVER, OK 73932 by (signature) <i>Howard Drilg Co.</i>

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.