

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Stevens

Location listed as:

Location changed to:

Section-Township-Range: 6-355-37W

6-355-37W

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): None Given

SW NE SW

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

verification method: Legal description, location of water right 42,250
listed in WIMAS database, and 2002 aerial photo of section.

initials: DRF date: 2/28/2005

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>SPRING</u>	$\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$	<u>6</u>	T <u>35</u> S	R <u>37</u> E/W

Distance and direction from nearest town or city street address of well if located within city?

15 mi S Hugoton

2 WATER WELL OWNER: <u>CARY COX</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>Rt 2 Box 47</u>	Application Number: <u>42,250</u>
City, State, ZIP Code: <u>ROLLA, KS 67954</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>662</u> ft. ELEVATION: <u>424.98</u> ft.
	Depth(s) Groundwater Encountered 1. <u>170</u> ft. 2. <u>170</u> ft. 3. <u>170</u> ft.
	WELL'S STATIC WATER LEVEL <u>170</u> ft. below land surface measured on mo/day/yr <u>4-24-98</u>
	Pump test data: Well water was <u>168</u> ft. after <u>1</u> hours pumping <u>1400</u> gpm
	Est. Yield <u>1400</u> gpm: Well water was <u>168</u> ft. after <u>1</u> hours pumping <u>1400</u> gpm
	Bore Hole Diameter: <u>25</u> in. to <u>662</u> ft., and <u>662</u> in. to <u>662</u> ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes <u>✓</u> No <u>✓</u> ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <u>✓</u> No <u>✓</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>✓</u> Clamped <u>✓</u>
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded <u>✓</u>	
2 PVC 4 ABS 7 Fiberglass Threaded <u>✓</u>	
Blank casing diameter <u>16</u> in. to <u>662</u> ft., Dia <u>16</u> in. to <u>662</u> ft., Dia <u>16</u> in. to <u>662</u> ft.	
Casing height above land surface <u>24</u> in., weight <u>250</u> lbs./ft. Wall thickness or gauge No. <u>250</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) <u>250</u>	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) <u>250</u>	
SCREEN-PERFORATED INTERVALS: From <u>292</u> ft. to <u>652</u> ft., From <u>292</u> ft. to <u>652</u> ft., From <u>292</u> ft. to <u>652</u> ft.	
GRAVEL PACK INTERVALS: From <u>10</u> ft. to <u>662</u> ft., From <u>10</u> ft. to <u>662</u> ft., From <u>10</u> ft. to <u>662</u> ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From <u>0</u> ft. to <u>10</u> ft., From <u>10</u> ft. to <u>662</u> ft., From <u>10</u> ft. to <u>662</u> ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? <u>South</u>	How many feet? <u>2630</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	180	SURFACE SAND & CLAY			
180	280	fine to med sand loose to tight w/ clay			
280	470	COARSE SAND + fine gravel			
470	480	CLAY			
480	500	COARSE SAND			
500	540	Red + GRAY CLAY			
540	575	Med to C. SAND w/ SANDY CLAY			
575	648	COARSE SAND			
648	662	Red CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-6-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>548</u> This Water Well Record was completed on (mo/day/yr) <u>5-13-98</u> under the business name of <u>LES TAYLOR DRILLING</u> by (signature) <u>Jimmie Blumpas</u>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.