


1 LOCATION OF WATER WELL: County: STEVENS 095 NE 1/4 NW 1/4 NE 1/4 Distance and direction from nearest town or city street address of well if located within city? LIBERAL WEST ON 2nd STREET TO 2nd STOP SIGN. SOUTH 2 MILES, 3/4 EAST & SOUTH INTO LOC.	Fraction	Section Number 16	Township Number T 35 S	Range Number R 37 EW
--	----------	----------------------	---------------------------	-------------------------

2 WATER WELL OWNER: RICHARD CLAGGETT RR#, St. Address, Box # : RFD #1 City, State, ZIP Code : HUGOTON, KS 67951	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 300 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 155 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 155 ft. below land surface measured on mo/day/yr 7-29-94 Pump test data: Well water was 175 ft. after 1 hours pumping 100 gpm Est. Yield 100 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 1/2 in. to 300 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No
---	---

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter 5 in. to 300 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 24 in. weight 2.902 lbs./ft. Wall thickness or gauge No. .265 SDR 21 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 240 ft. to 300 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 200 ft. to 300 ft. From ft. to ft. From ft. to ft. From ft. to ft.	CASING JOINTS: Glued X Clamped Welded Threaded
--	--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 1 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?	HOLE PLUG
--	-----------

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	SANDY CLAY	196	203	SAND STONE
2	14	SANDY CLAY	203	213	SAND
14	32	CLAY	213	225	COARSE SAND
32	38	SANDY CLAY	225	235	SAND
38	45	SAND	235	246	SANDY CLAY
45	69	CLAY	246	275	SAND
69	103	SANDY CLAY & CLAY	275	292	SAND & MD. SAND
103	112	SANDY CLAY	292	300	RED & YELLOW CLAY
112	126	SAND			
126	151	SANDY CLAY & CALICHE			
151	162	CLAY & CALICHE			
162	171	SANDY CLAY			
171	178	CALICHE CLAY & SAND STONE			
178	190	SANDY CLAY			
190	196	SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-29-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 7-29-94 under the business name of HOWARD DRLG.CO.BOX 806 BEAVER, OK 73932 by (signature)
