

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Stevens	SE 1/4 SE 1/4 NW 1/4	6	T 35 S	R 38 E <u>W</u>

Distance and direction from nearest town or city street address of well if located within city?

8 miles south - 1 west of Feterita, KS.

2 WATER WELL OWNER:	Kramer Enterprises	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	% Jim Kramer	Application Number:
City, State, ZIP Code :	1114 S. Monroe, Hugoton, KS. 67951	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 42.0 ft. ELEVATION: slope
	Depth(s) Groundwater Encountered 1. 17.0 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 17.0 ft. below land surface measured on mo/day/yr 1/29/96
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 6 in. to 42.0 ft., and in. to ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	Observation
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
<u>2 PVC</u> 4 ABS 7 Fiberglass Threaded	
Blank casing diameter 2 in. to 38.0 ft., Dia in. to ft., Dia in. to ft.	
Casing height above land surface 24 in., weight schedule 40 lbs./ft. Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped <u>9 Drilled holes</u>	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 380 ft. to 420 ft., From ft. to ft.	
GRAVEL PACK INTERVALS: From 20 ft. to 420 ft., From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement <u>2 Cement grout</u> 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage none	
Direction from well?	How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	20	Clat			
20	60	Fine sand			
60	100	Fine to medium sand w/clay breakers			
100	150	Medium to coarse sand w/clay breakers			
150	260	Brown clay			
260	275	Fine sand			
275	340	Brown clay			
340	420	Fine to medium sand w/clay breakers			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-28-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>164</u> This Water Well Record was completed on (mo/day/yr) 6/24/96 under the business name of Houck Bros. Drilling Co. by (signature) M. Beard
--