

1 LOCATION OF WATER WELL: County: STEVENS	Fraction NE 1/4 NE 1/4 SE 1/4	Section Number 1	Township Number T 35 S	Range Number R 38 E/W
---	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

9 miles south 2 West of Hugoton, KS

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Roy Cox Rella, KS 67954	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 560 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 179 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 179 ft. below land surface measured on mo/day/yr 7-18-96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 7/8 in. to 560 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 2 in. to 520 ft. Dia. in. to ft. Dia. in. to ft.			
Casing height above land surface 26 in., weight Schedule 40 lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass	8 Saw cut	11 None (open hole)	
6 Concrete tile	9 Drilled holes	10 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	4 Key punched		
2 Louvered shutter			
3 Mill slot			
4 Key punched			
5 Gauzed wrapped			
6 Wire wrapped			
7 Torch cut			
SCREEN-PERFORATED INTERVALS: From 520 ft. to 560 ft., From ft. to ft., From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 560 ft., From ft. to ft., From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage	NONE		
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well?	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	40	Fine sand			
40	90	Fine sand w/rock shells			
90	130	Brown clay			
130	190	Brown clay w/hard rock			
190	210	Sandy clay + fine sand			
210	265	Coarse sand w/cemented strips			
265	281	Brown + gray clay w/fine sand			
281	310	Medium sand, very loose			
310	350	Blue + yellow clay w/fine sand			
350	380	Blue clay w/fine sand strips			
380	560	Coarser sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-18-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 164 This Water Well Record was completed on (mo/day/yr) 7-18-96 under the business name of Houck Bros. by (signature) M. Beard
