

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Stevens	NW 1/4 NW 1/4 SE 1/4	11	T 35 S	R 38 EW

Distance and direction from nearest town or city street address of well if located within city?

10 1/2 miles south, 3 west of Hugoton, Kansas

2 WATER WELL OWNER:	Kramer Enterprises	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	% James Kramer	Application Number:
City, State, ZIP Code :	1104 So. Monroe, Hugoton, Ks, 67951	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 504.6 ft. ELEVATION: slope
	Depth(s) Groundwater Encountered 1. 178 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 178 ft. below land surface measured on mo/day/yr 5-6-97
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 24 in. to 504 ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes X No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 16 in. to 244.6 ft., Dia 16 in. to 364.6 ft., Dia			Threaded
Casing height above land surface 20 in., weight 36.91 lbs./ft. Wall thickness or gauge No. 219			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:		From 244.6 ft. to 444.6 ft.	From 364.6 ft. to 504.6 ft.
GRAVEL PACK INTERVALS:		From 20 ft. to 504.6 ft.	From 504.6 ft. to 504.6 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	None

Direction from well?		How many feet?	
FROM	TO	LITHOLOGIC LOG	PLUGGING INTERVALS
0	2	Surface	
2	20	Sandy clay	
20	30	Clay	
30	100	Sandy clay w/sand strips	
100	100		
30	100	Sandy clay w/sand strips	
100	135	Red clay w/coarse sand strips	
135	195	Sandy clay w/fine sand	
195	225	Medium to coarse sand w/clay breakers	
225	270	Coarse sand w/small gravel	
270	283	Sandy clay	
283	365	Coarse sand w/small gravel	
365	440	Red sandy clay w/very fine sand	
440	500	Medium sand	
500	506	Red clay	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (2) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-6-97 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 164 This Water Well Record was completed on (mo/day/yr) 5-13-97
under the business name of Huck Bros Drig by (signature) M. Beard