

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Stevens	SE ¼ SE ¼ SW ¼	8	T 35 S	R 38 E W

Distance and direction from nearest town or city street address of well if located within city? North of Guymon at HWY 136 & Ks State

Line go 1 mi N E .5 flag on pole at East end of evergreen trees on N side

2 WATER WELL OWNER:	EOG Resources Inc	8-1 Ansley HJV
RR#, St. Address, Box # :	3817 NW Wxpy Ste 500	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Oklahoma City, Ok 73112	Application Number: 2005/0386

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 360 ft. ELEVATION:
--	--

N

1	2
3	4
5	6
7	8
9	10
11	12

W E

S

Depth(s) Groundwater Encountered 1. 285 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 285 ft. below land surface measured on mo/day/yr 12-16-05

Pump test data: Well water was 290 ft. after 1 hours pumping 100 gpm

Est. Yield 100 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
7 Domestic (lawn & garden) 10 Monitoring well				

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 6 in. to 3.80 in. Dia	ft. Dia	ft. Dia	in. to ft.
Casing height above land surface +2 in., weight 4.074 lbs./ft.	Wall thickness or gauge No. SDR 21.316		
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-Cement	
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS
			11 Other (Specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Guazed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 280 ft. to 360 360	ft. to ft.	
GRAVEL PACK INTERVALS:	From 180 ft. to 360	ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Hole Plug
Grout Intervals: From 1 ft. to 25 ft., From	ft. to ft.	ft. to ft.	ft. to ft.	ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				How many feet?
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Surface Clay			
8	73	Clay/sandy clay			
73	104	Sandy clay			
104	168	Clay			
168	197	Sand/clay streaks			
197	252	Sandy clay			
252	276	Sand			
276	285	Clay			
285	310	Medium sand			
310	318	Clay			
318	338	Sand			
338	353	Course sand			
353	360	Tan/pink clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-16-05 and this record is true to the best of my knowledge and belief. Kansas Water Contractor's Licence No KWWCL 430 This Water Well Record was completed on (mo/day/year) 12-16-05 under the business name of Howard Drilling Co Box 806 Beaver, Ok 73932 by (signature) Howard Drilling Co
--