

1 LOCATION OF WATER WELL: County: Stevens	Fraction SE ¼ SE ¼ NW ¼	Section Number 6	Township Number T 35 S	Range Number R 38 E/W
--	----------------------------	---------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

8 miles south of Feteria and ½ west

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Kramer Properties 1004 S. Monroe Hugoton, Kansas 67951	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 59.5 ft. ELEVATION: slope
	Depth(s) Groundwater Encountered 1. 2.26 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 2.26 ft. below land surface measured on mo/day/yr 6./10/98 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 1800 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 24 in. to 59.5 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded X
Blank casing diameter 16 in. to 44.8 ft. Dia 16 in. to 50.0 ft. Dia 16 in. to 59.5 ft.			Threaded
Casing height above land surface 18 in. weight 36.9 lbs./ft. Wall thickness or gauge No. 21.9			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 4.48 ft. to 46.8 ft. From 50.0 ft. to 58.0 ft.			
GRAVEL PACK INTERVALS: From 2.0 ft. to 59.5 ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 2.0 ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	none
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface	590	600	Red bed
2	20	Clay			
20	60	Fine sand			
60	100	Fine to medium sand w/clay breakers			
100	150	Medium to coarse sand w/clay breakers			
150	260	Brown clay			
260	275	Fine sand			
275	340	Brown clay			
340	438	Fine to medium sand			
438	468	Medium sand			
468	500	Fine to medium sand w/clay breakers			
500	530	Coarse sand			
530	570	Coarse sand w/clay breakers			
570	583	Coarse sand			
583	590	Brown and red clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6./10/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 164 This Water Well Record was completed on (mo/day/yr) 6./18/98 under the business name of Houck Bros. Drilling Co by (signature) M. Beard
--