

1 LOCATION OF WATER WELL: County: Stevens	Fraction SE 1/4 SE 1/4 NW 1/4	Section Number 6	Township Number T 35 S	Range Number R 38 E/W
--	----------------------------------	---------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

8 miles south and 1/2 west of Feteria, Ks.

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Kramer Properties 1004 S. Monroe Hugoton, Kansas 67951	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 59.5 ft. ELEVATION: slope
	Depth(s) Groundwater Encountered 1. 22.6 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 22.6 ft. below land surface measured on mo/day/yr 6/11/98. Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 7/8 in. to 59.5 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 2 in. to 4.48 ft. Dia. in. to ft. Dia. in. to ft.			
Casing height above land surface 2.0 in. weight schedule 8.0 PVC lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 4.48 ft. to 59.5 ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 2.0 ft. to 59.5 ft. From ft. to ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 2.0 ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage	None		
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well?	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface	590	600	Red bed
2	20	Clay			
20	60	Fine sand			
60	100	Fine to medium sand w/clay breakers			
100	150	Medium to coarse sand w/clay breakers			
150	260	Brown clay			
260	275	Fine sand			
275	340	Brown clay			
340	438	Fine to medium sand			
438	468	Medium sand			
468	500	Fine to medium sand w/clay breakers			
500	530	Coarse sand			
530	570	Coarse sand w/clay breakers			
570	583	Coarse sand			
583	590	Brown and red clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/11/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 164 This Water Well Record was completed on (mo/day/yr) 6/18/98 under the business name of Houck Bros. Drlg. by (signature) M. Beard
