

1 LOCATION OF WATER WELL: County: Stevens	Fraction NW ¼ NW ¼ NE ¼	Section Number 2	Township Number T 35 S	Range Number R 39 E/W
--	----------------------------	---------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

8 south 2½ west of Feteria, Ks

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Kramer Properties 1004 S. Monroe Hugoton, Kansas 67951	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 520 ft. ELEVATION: slope
	Depth(s) Groundwater Encountered 1. 254 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 254 ft. below land surface measured on mo/day/yr 4/26/98 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9.7/8 in. to 520 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 2 in. to 18.1 ft., Dia.			11 Other (specify)
Casing height above land surface 1.7 in., weight schedule 8.0 PVC lbs./ft. Wall thickness or gauge No.			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
GRAVEL PACK INTERVALS:			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 20 ft.			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	10	Clay			
10	85	Fine sand w/small clay breakers			
85	105	Sandy clay			
105	130	Coarse sand			
130	178	Sandy clay			
178	205	Gray clay			
205	360	Brown clay w/fine sand strips			
360	400	Fine sand w/small clay breakers			
400	440	Sandy clay w/fine to medium sand strips			
440	485	Fine to medium sand w/small clay breakers			
485	520	Brown clay w/strips of red sandrock			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/26/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 164 This Water Well Record was completed on (mo/day/yr) 5/5/98 under the business name of Houck Bros, Drilling Co by (signature) Mr. Beard
