WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

		T	Т			T
1. Location of well:	County Fraction			Section number		Township number Range number
1. Localion of Well:	Martan	WEYANEYASU	21/4		4	T 35 s R 39 E/W
2. Distance and direct	ction from nearest town or city:	South	3. Owner			ill Light
Street address of well location if in city:						
City, star				e, zip c	ode:	KollA, Kon
4. Locate with "X" in section below: N						6. Bore hole dia. 25 in. Completion date Well depth 553 ft
i !!!						7 Cable tool 🗶 Rotary Driven Dug
						Hollow rod Jetted Bored Reverse rotary
						8. Use: Domestic Public supply Industry
						Irrigation Air conditioning Stock
SW SE						LawnOil field water Other 9. Casing: Material Stock Height: Above or below
						Threaded Welded isurface in.
s						RMPPVCWeight #2.5_lbs./ft.
1 Mile ————						Dia 16 in. to 553ft. depth Wall Thickness: inches or
5. Type and color of	material			From	То	Diain. toft. depth gage No250
·						10. Screen: Manufacture's name
Overburder	1	 		믹		Type Steel Dia. 16"
Top Soil				2	200	Slot/gauze Length
						Set betweenft.
Fine Sd. & Clay			- 2	200	270	Gravel pack? Size range of material 14-14
Fine Sd. F	Rock & Sd.Stone		2	270	340	11. Static water level: mo./day/yr.
Fine & Med. Sd.				340	420	12. Pumping level below land surfaces: NA
						ft. after hrs. pumping g.p.m.
Med. & Coa	arse Sd.		- '	+20	440	ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.
Med. & Fir	ne 5d.		l	440	480	13. Water sample submitted: mo./day/yr.
Med. & Coa	arse Sd.		Į.	480	490	Yes A No Date 14. Well head completion:
Med. & Fine Sd.				490	540	Pitless adapter//# Inches above grade
				,		15. Well grouted? 4 & S With: X Neat cement Bentonite Concrete
Fine & Coarse Sd.			!	540	550	Depth: From ft. to ft.
Red Clay	······································		!	550	568	
						Well disinfected upon completion? YesNo
	***************************************					17. Pump: Not installed
						Manufacturer's name HP Volts
						Length of drop pipe ft. capacityg.p.m.
				1		Type:
						Submersible Turbine
	(Use a second s	heet if needed)				Jet Reciprocating Other S
18. Elevation:	19. Remarks: 10			·•		20. Water well contractor's certification:
16+ Cacpland 480-440 Scaced 440-480						This well was drilled under my jurisdiction and this report
Topography: 480-490 Screen						is true to the best of my knowledge and belief. KTM Drilling. Mc. 225 \$\
HIII 490-540						Business pame License No.
Slope 540-550 Scacen					1	1 1 / / / / / / / / / / / / / / / / / /
- Upland 100 Johnson Fer,					ا ہے	Signed Authorized representative
Valley 16" Strol 1000 S/01					/	L CONTROLLED TOPICS CHILDREN