

361248

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: MORTON	SW 1/4 NE 1/4 NW 1/4 SW 1/4	16	T 35 S	R 42 EW ①

Distance and direction from nearest town or city street address of well if located within city?

614 MORTON ELKHART

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : DON RASH	Application Number:
City, State, ZIP Code : 615 EAST CEDAR	
LIBERAL KS 67901	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 212 ft. ELEVATION: 3605.70
	Depth(s) Groundwater Encountered ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 194.24 ft. below land surface measured on mo/day/yr 3-16-05 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) ① Monitoring well m.w.-9 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded X
② PVC	7 Fiberglass		Threaded X
3 RMP (SR)			
4 ABS			
Blank casing diameter in. to 182 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No 5440			
TYPE OF SCREEN OR PERFORATION MATERIAL:	⑦ PVC	10 Asbestos-Cement	
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify) ft.	
③ Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 182 ft. to 212 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 178 ft. to 212 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 178 ft. to 212 ft., From 0 ft. to 178 ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage			
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well?	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	CONCRETE/FILL			
2	10	SANDY CLAY - DK BLN			
10	50	CLAYEY SAND - FINE			
50	70	CLAYEY SAND - FINE			
70	180	SANDY CLAY w/ CALICHE			
180	200	TRACE FINE SAND			
180	200	SILTY SAND - f to COARSE			
200	212	SANDY CLAY w/ CALICHE + f - COARSE SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-22-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No SS4 This Water Well Record was completed on (mo/day/yr) 3/28/05 under the business name of Wafte Ruppwell by (signature) Wafte Ruppwell
--