


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: MORTON	SW 1/4 NE 1/4 NW 1/4 SW	116	T 35 S	R 42 E/W

Distance and direction from nearest town or city street address of well if located within city?

1614 MORTON Eikhart

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : DON RASH	Application Number:
City, State, ZIP Code : 615 E CEDAR LIBERTY, KS 67901	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 210 ft. ELEVATION: 3596.80
	Depth(s) Groundwater Encountered 1 128.96 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well MW-20
	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
2 PVC	4 ABS	7 Fiberglass	Threaded X
Blank casing diameter in. to 4 in. to 180 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	7 PVC	10 Asbestos-Cement
1 Steel	3 Stainless Steel	8 RMP (SR)	11 Other (Specify)
2 Brass	4 Galvanized Steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	ft.
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 180 ft. to 210 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 176 ft. to 210 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 176 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
Fill	15	SILTY CLAY, DARK BROWN			
15	40	SILTY SAND, fine-med, yellow brown w/ trace clay + caliche			
40	60	SILTY CLAY, gray, dense, w/caliche + sand			
60	70	SILTY SAND, fine-med, y brn w/ lt brn clay + caliche			
70	147	SANDY CLAY, red brn, dense w/caliche			
147	155	SAND, fine-med, w/ trace clay + caliche			
155	165	SANDY CLAY, brn w/caliche			
165	168	SANDY CLAY, red brn, very dense w/caliche			
168	210	SAND, fine-coarse, w/sandy clay + caliche			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/2/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 554 This Water Well Record was completed on (mo/day/yr) 10-30-05 under the business name of Woodstar Pumps & Well by (signature) Jay Wampler
