

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Morton Fraction NE 1/4 NW 1/4 SW 1/4 Section Number 16 Township Number T 35 S Range Number R 42 E/W

Distance and direction from nearest town or city street address of well if located within city? Intersection of Stillman & Stevens St Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: 37°00'17.0" Longitude: 101°53'35.2"

2 WATER WELL OWNER: RR#, St. Address, Box #: Don Rash, 615 East Cedar, Liberal, KS 67901 Elevation: Datum: Data Collection Method:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with 'X' in the NW quadrant] 4 DEPTH OF COMPLETED WELL .210 ft. Depth(s) Groundwater Encountered (1) 186.3 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 186.3 ft. below land surface measured on mo/day/yr 09-07-06 Pump test data: Well water was...ft. after... hours pumping... gpm Est. Yield .2 gpm: Well water was...ft. after... hours pumping... gpm

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought Iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below) CASING JOINTS: Glued, Clamped, Welded, Threaded

Blank casing diameter 4.5 in. to...ft., Diameter...in. to...ft., Diameter...in. to...ft. Casing height above land surface...in., Weight 2.70 lbs./ft. Wall thickness or gauge No. Sch 40 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RM (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Guazed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw Cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 180 ft. to 210 ft., From...ft. to...ft., From...ft. to...ft.

GRAVEL PACK INTERVALS: From 175.4 ft. to 210 ft., From...ft. to...ft., From...ft. to...ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other, Cement Grout Intervals: From 175.4 ft. to 2 ft., From...ft. to...ft., From 2.0 ft. to 0.0 ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer Storage, 13 Insecticide Storage, 14 Abandoned water well, 15 Oil well/gas well, 16 Other (specify below)

Direction from well? East How many feet? 45

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-2 Topsoil & Silt, 2-12 Silt, 12-40 Sand, 40-120 Sandy Silt, 120-150 Sand, 150-152 Chert layer in calcium carbonate, 152-173 Sand & Gravel, 173-190 Sandy silt, 190-210 Sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09-07-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/year) 09-13-09 under the business name of Woofter Pump & Well, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.