(to rectify lacking or incorrec	t information) County: Morton
Location listed as:	Location changed to:
Section-Township-Range: None listed	17-35-42W
Fraction (1/4 1/4 1/4): none listed	SE
Other changes: Initial statements:	
Changed to:	
Comments:	
verification method: Used County maps a	nd Mapquest to
verify location.	
,	initials: \(\frac{\mathcal{B}}{\mathcal{B}} \) date: \(\frac{8/5/2008}{\tag{8}} \)

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

LOCATION OF WATER WELL: Fraction COUNTY: MORTON 1/4 1/4 1/4	; Section Number	er ¦ Towr ¦ T	iship Number S	¦ Range A ¦ R	lumber
Distance and direction from nearest town or city street address 1110 S. MUNCY AVE. ELKHART, KS 67950-	s of well if locat	ed within ci	ty?		
WATER WELL OWNER: FARRINGTON, E.R. RR≸, St. Address, Box ≢ : 1110 S. MUNCY AVE. City, State, ZIP code : ELKHART, KS 67950-	Board c Applica	of Agricultur Ition Number:	e, Division	of Water Reso	urces
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WEL AN "X" IN SECTION BOX: Depth(s) Groundwater E	LL 365 ELEV Encountered	ATION: 0 1. 0 ft.	2.	0 ft. 3.	0 f
WELL'S STATIC WATER LEVE Pump testdata:	EL 255 ft. below : Well water was				
Estimated Yield 30 gp	pm: Well water was	0 ft. a	fter 0 h	ours pumping	0 9
₩ E Bore Hole Diameter	10 in. to	365 ft., and	in. t	o 0 ft.	
SW SE	S: LAWN & GARDEN				f I
Was a chemical/bacterio	logical sample sub	mitted to de	partment? No	;	rted?
YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS lank casing diameter 5 in. to 365 ft., Dia asing height above land surface 12 in., weight 200 in the surface 200 in the su	e was submitted S: CERTA-LOC in. to 0 ft.,	Di a i	n. to 0		
YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS lank casing diameter 5 in. to 365 ft., Dia asing height above land surface 12 in., weight 200 i YPE OF SCREEN OR PERFORATION MATERIAL: PVC CREEN OR PERFORATION OPENINGS ARE: SAW CUT CREEN PERFORATED INTERVALS: From 280 ft. to 360 ft. From 0 ft. to 0 ft.	e was submitted S: CERTA-LOC in. to 0 ft., lbs/ft. Wall thic ft., From 0 ft ft., From 0 ft	Dia ickness or gau	n. to 0 ige No. 21 t.		
YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS lank casing diameter 5 in. to 365 ft., Dia asing height above land surface 12 in., weight 200 l YPE OF SCREEN OR PERFORATION MATERIAL: PVC CREEN OR PERFORATION OPENINGS ARE: SAW CUT CREEN PERFORATED INTERVALS: From 280 ft. to 360 ft GRAVEL PACK INTERVALS: From 28 ft. to 365 ft From 0 ft. to 0 ft	e was submitted S: CERTA-LOC in. to 0 ft., lbs/ft. Wall thic ft., From 0 ft ft., From 0 ft ft., From 0 ft	Dia ickness or gau	n. to 0 ige No. 21 t. t.		
YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS lank casing diameter 5 in. to 365 ft., Dia asing height above land surface 12 in., weight 200 i YPE OF SCREEN OR PERFORATION MATERIAL: PVC CREEN OR PERFORATION OPENINGS ARE: SAW CUT CREEN PERFORATED INTERVALS: From 280 ft. to 360 ft. From 0 ft. to 0 ft. GRAVEL PACK INTERVALS: From 28 ft. to 365 ft. FROMT MATERIAL BENTONITE rout Intervals: From 5 ft. to 28 ft., From 0 ft. hat is the nearest source of possible contamination: NONE	e was submitted S: CERTA-LOC in. to 0 ft., lbs/ft. Wall thic ft., From 0 ft ft., From 0 ft ft., From 0 ft	Dia ickness or gau	n. to 0 ige No. 21 t. t. t.	ft.	
YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS lank casing diameter 5 in. to 365 ft., Dia asing height above land surface 12 in., weight 200 i YPE OF SCREEN OR PERFORATION MATERIAL: PVC CREEN OR PERFORATION OPENINGS ARE: SAW CUT CREEN PERFORATED INTERVALS: From 280 ft. to 360 f From 0 ft. to 0 f GRAVEL PACK INTERVALS: From 28 ft. to 365 f From 0 ft. to 0 f ROUT MATERIAL BENTONITE rout Intervals: From 5 ft. to 28 ft., From 0 ft. hat is the nearest source of possible contamination: NONE irection from well?	e was submitted S: CERTA-LOC in. to	Dia ickness or gau	n. to 0 ige No. 21 t. t. t. t. t.	ft. How many fe	
YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS lank casing diameter 5 in. to 365 ft., Dia lasing height above land surface 12 in., weight 200 in lasing height above land surface 12 in., weight 200 in lasing height above land surface 12 in., weight 200 in lasing height above land surface 12 in., weight 200 in last casing height above land surface 12 in., weight 200 in last casing height above land surface 12 in., weight 200 in last casing height above land surface 12 in., weight 200 in last casing Joints From 28 ft. to 360 in last casing Joints From 0 ft. to 0 in last casing Joints From 28 ft. to 365 in last casing Joints From 0 ft. to 0 in last casing Joints From 0 ft. to 360 in last casing Joints From 0 ft. to 360 in last casing Joints From 0 ft. to 360 in last casing Joints From 0 ft. to 360 in last casing Joints From 1 ft. to 360 in last casing Joints From 1 ft. to 360 in last casing Joints From 1 ft. to 360 in last casing Joints From 1 ft. to 360 in last casing Joints From 1 ft. to 360 in last casing Joints From 1 ft. to 360 in last casing Joints From 2 ft. to 360 in last casing Joints From 2 ft. to 360 in last casing Joints From 2 ft. to 360 in last casing Joints From 2 ft. to 360 in last casing Joints From 2 ft. to 360 in last casing Joints From 2 ft. to 360 in last casing Joints From 2 f	e was submitted S: CERTA-LOC in. to	Dia ickness or gau	n. to 0 ige No. 21 t. t. t. t. t.	ft.	
PE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS and casing diameter 5 in. to 365 ft., Dia using height above land surface 12 in., weight 200 PE OF SCREEN OR PERFORATION MATERIAL: PVC CREEN OR PERFORATION OPENINGS ARE: SAW CUT CREEN PERFORATED INTERVALS: From 280 ft. to 360 ft. to 0	e was submitted S: CERTA-LOC in. to	Dia ickness or gau	n. to 0 ige No. 21 t. t. t. t. t.	ft. How many fe	
YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS lank casing diameter 5 in. to 365 ft., Dia asing height above land surface 12 in., weight 200 l YPE OF SCREEN OR PERFORATION MATERIAL: PVC CREEN OR PERFORATION OPENINGS ARE: SAW CUT CREEN PERFORATED INTERVALS: From 280 ft. to 360 f	e was submitted S: CERTA-LOC in. to	Dia ickness or gau	n. to 0 ige No. 21 t. t. t. t. t.	ft. How many fe	
YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS lank casing diameter 5 in. to 365 ft., Dia asing height above land surface 12 in., weight 200 l YPE OF SCREEN OR PERFORATION MATERIAL: PVC CREEN OR PERFORATION OPENINGS ARE: SAW CUT CREEN PERFORATED INTERVALS: From 280 ft. to 360 f	e was submitted S: CERTA-LOC in. to	Dia ickness or gau	n. to 0 ige No. 21 t. t. t. t. t.	ft. How many fe	

completed on (mo/day/year) 09/07/07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179

This Water Well Record was completed on (mo/day/yr) 10/12/07 under the business name of JOE'S WELL SERVICE, INC.

by (signature)

(Continued)-WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: | Section Number ! Township Number 1/4 1/4 1/4 COUNTY: MORTON ¦ T S FARRINGTON, E.R. RR#, St. Address, Box # : 1110 S. MUNCY AVE. Board of Agriculture, Division of Water Resources City, State; ZIP code : ELKHART, KS 67950-Application Number: TO ! FROM ! LITHOLOGIC LOG 200 240 ; 32 TAN CLAY 02 FINE SAND 19 LAYERS 260 | 32 TAN CLAY 02 FINE SAND 29 SANDSTONE 240 280 | 29 SANDSTONE 26 RED CLAY 29 SANDSTONE 320 | 29 SANDSTONE 260 280 320 340 | 29 SANDSTONE 26 RED CLAY 19 LAYERS 340 360 | 29 SANDSTONE 20 RED SHALE 360 380 ! 20 RED SHALE

TOONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 09/07/07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179

This Water Well Record was completed on (mo/day/yr) 10/12/07 under the business name of JOE'S WELL SERVICE, INC.

by (signature)