

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number																
COUNTY: MORTON		SE 1/4 SE 1/4 SW 1/4	25	T 35 S	R 43 W																
Distance and direction from nearest town or city street address of well if located within city? FROM ELKHART, KS. - 2 M. ON HIGHWAY 27, 2 W, 1 N AND 1/2 W.																					
2 WATER WELL OWNER:		Well # 2 - 86																			
RR#, St. Address, Box # : P.O. BOX J		Board of Agriculture, Division of Water Resources																			
City, State, ZIP code : ELKHART, KS 67950-		Application Number:																			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 145 ELEVATION: 0																			
<table border="1" style="width:100%; text-align: center;"> <tr><td colspan="4"> </td></tr> <tr><td colspan="2">NW</td><td colspan="2">NE</td></tr> <tr><td colspan="2">SW</td><td colspan="2">SE</td></tr> <tr><td colspan="4">X</td></tr> </table>						NW		NE		SW		SE		X				Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.			
		NW		NE																	
		SW		SE																	
		X																			
WELL'S STATIC WATER LEVEL 85 ft. below land surface measured on mo/day/yr 06/07/95																					
Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm																					
Estimated Yield 25 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm																					
Bore Hole Diameter 9 in. to 145 ft., and in. to 0 ft.		WELL WATER TO BE USED AS: DOMESTIC																			
Was a chemical/bacteriological sample submitted to department? No ;		If yes, mo/day/yr sample was submitted Water well disinfected? Yes																			
5 TYPE OF BLANK CASING USED: PVC		CASING JOINTS: GLOUED																			
Blank casing diameter 5 in. to 145 ft., Dia in. to 0 ft., Dia in. to 0 ft.		Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21																			
TYPE OF SCREEN OR PERFORATION MATERIAL: PVC		SCREEN OR PERFORATION OPENINGS ARE: SAW CUT																			
SCREEN PERFORATED INTERVALS:		From 110 ft. to 140 ft., From 0 ft. to 0 ft.																			
GRAVEL PACK INTERVALS:		From 0 ft. to 0 ft., From 0 ft. to 0 ft.																			
		From 40 ft. to 145 ft., From 0 ft. to 0 ft.																			
		From 0 ft. to 0 ft., From 0 ft. to 0 ft.																			
6 GROUT MATERIAL BENTONITE																					
Grout Intervals: From 0 ft. to 40 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.																					
What is the nearest source of possible contamination: NONE - NEW SITE																					
Direction from well?		How many feet? 0																			
FROM TO LITHOLOGIC LOG FROM TO PLOGGING INTERVALS																					
0	20	TOPSOIL SANDY CALACHIE																			
20	42	BROWN CLAY																			
42	90	CALACHIE CLAY																			
90	120	FINE SAND CLAY																			
120	130	FINE SAND RED BED																			
130	145	RED BED																			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 06/07/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 08/17/95 under the business name of JOB'S WELL SERVICE, INC. by (signature) <i>Justin Creek</i>																					