

1 LOCATION OF WATER WELL: Fraction	Section Number	Township Number	Range Number
County: Jewell ¼ SE ¼ SE ¼	25	T 3 S	R 10 EW

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Gail Colson  
 RR#, St. Address, Box #: AA 2 Box 88  
 City, State, ZIP Code: Manhattan, KS 66695  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
--NW--			--NE--
W			E
--SW--			--SE--
S			

4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION: \_\_\_\_\_

Depth(s) Groundwater Encountered 1 \_\_\_\_\_ ft. 2 \_\_\_\_\_ ft. 3 \_\_\_\_\_ ft.  
 WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr \_\_\_\_\_  
 Pump test data: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 Est. Yield 5 gpm; Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 WELL WATER TO BE USED AS:  
 Domestic     Feedlot     Oil field water supply     Air conditioning     Injection well  
 Irrigation     Industrial     Domestic (lawn & garden)     Dewatering     Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes \_\_\_\_\_ No ; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected?  Yes    No

5 TYPE OF BLANK CASING USED:  
 Steel     RMP (SR)     Wrought iron     Concrete tile    CASING JOINTS:  Glued     Clamped  
 PVC     ABS     Asbestos-Cement     Other (specify below)     Welded  
 Fiberglass     Threaded

Blank casing diameter 2.5 in. to 4.0 ft., Dia \_\_\_\_\_ in. to \_\_\_\_\_ ft., Dia \_\_\_\_\_ in. to \_\_\_\_\_ ft.  
 Casing height above land surface 12 in., weight \_\_\_\_\_ lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 Steel     Stainless Steel     Fiberglass     PVC     Asbestos-Cement  
 Brass     Galvanized Steel     Concrete tile     RMP (SR)     Other (Specify) \_\_\_\_\_  
 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 Continuous slot     Mill slot     Guazed wrapped     Saw cut     None (open hole)  
 Louvered shutter     Key punched     Wire wrapped     Drilled holes  
 Torch cut     Other (specify) \_\_\_\_\_ ft.

SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 50 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

6 GROUT MATERIAL:  Neat cement     Cement grout     Bentonite     Other \_\_\_\_\_

Grout Intervals: From 0 ft. to 20 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

What is the nearest source of possible contamination:  
 Septic tank     Lateral lines     Pit privy     Livestock pens     Abandoned water well  
 Sewer lines     Cess pool     Sewage lagoon     Fuel storage     Oil well/Gas well  
 Watertight sewer lines     Seepage pit     Feedyard     Insecticide storage     Other (specify below) none

Direction from well? \_\_\_\_\_ How many feet? \_\_\_\_\_

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	30	Topsoil & Clay			
30	40	Blue Clay			
40	45	Blue Clay w/ Broken Rock			
45	50	Gray shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed,  reconstructed, or  plugged under my jurisdiction and was completed on (mo/day/year) 4/27/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 741 This Water Well Record was completed on (mo/day/yr) 5/12/05 under the business name of Watson Well Drilling by (signature) Edu Watson

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.