

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction SW ¼ NW ¼ NW ¼	Section Number 10	Township Number T 3 S	Range Number R 11 W E/W
County: Smith				

Distance and direction from nearest town or city street address of well if located within city?

Chicago Avenue and Elm Street

2 WATER WELL OWNER:	Joe's Service	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	RR 2, Box 32	Application Number:
City, State, ZIP Code :	Lebanon, Kansas 66952	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION: 1822 ft.
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 17.3 ft. below land surface measured on mo/day/yr 3/20/95
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield NA gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 27 in. to in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
	2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
	Blank casing diameter 2 in. to 12 in. to ft., Dia in. to ft., Dia in. to ft.	7 Fiberglass			Threaded X
	Casing height above land surface -3.7 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40				
TYPE OF SCREEN OR PERFORATION MATERIAL:					
	1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
	2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:					
	1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
	2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS:					
	From 12 ft. to 27 ft., From ft. to ft.				
GRAVEL PACK INTERVALS:					
	From 10 ft. to 27 ft., From ft. to ft.				

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From 0 ft. to 8 ft., From 8 ft. to 10 ft., From 10 ft. to ft.				
What is the nearest source of possible contamination:				
	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				UST Basin
Direction from well? SW				How many feet? 65

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Concrete,			MW4
0.5	2	(Fill) Clay, Medium brown			GeoCore # 101 Flush-mount Cover
2	11	Silt, Light Brown-Gray			KDHE # U6092494 Tag # 126377
11	13	Clay, Dark Brown			
13	16	Clay, Dark Brown-Gray Green Mottled			
16	18	Clay, Light Olive-Yellow Brown			
18	23	Shale, Light Gray			
23	24.5	Clay, Light Orange-Brown			
24.5	27	Shale, Light Gray Light Red-Brown			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/20/95	and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 527	This Water Well Record was completed on (mo/day/yr) 4/6/95
under the business name of GeoCore Services, Inc.	by (signature) <i>Dale Kelly</i>

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.