WATER WELL RECORD	Form W	WC-5	Division of Water	r Resources App. N	0.
1 LOCATION OF WATER WE County: SMITH	NW 1/4 NW 1/4	1/4 1/4	Section Number 31	Township No. T 3 S	Range Number R 13 ☐E ☑W
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:					
from nearest town or intersection	Latitude:394	1515.3	(in decimal degrees)		
	Longitude: 098 50 27.9 (in decimal degrees) Elevation:				
			Datum: WGS 84	I D NAD 92 D	 NIAIN 07
2 WATER WELL OWNER: E	ВОВ ЕМСН		Collection Method:	+, □ NAD 83, □	NAD 27
RR#, Street Address, Box #: 1	8022 M ROAD		GPS unit (Mak	e/Model:	,)
City, State, ZIP Code : S	MITH CENTER		Digital Map/Pho	oto, 🔲 Topographic	c Map. And Survey
3 LOCATE WELL			Est. Accuracy: 🔲 <	3 m, 🔲 3-5 m, 🔲	5-15 m, $\square$ >15 m
WITH AN "X" IN 4 DEPT	H OF COMPLETED WELL	L 70	ft		
SECTION BOX: Depth(s)	Depth(s) Groundwater Encountered (1) ft (2) ft (3)				
N WELL'S	STATIC WATER LEVEL	ft be	low land surface n	neasured on mold	257/572
	Pump test data: Well wate	r was. AIR DVL	ft. after	hours numr	ning onm
White I will be the second of					ning gnm
W Bore Hole Diameter 11.5 in. to .20 ft., and .9.0 in. to .70 ft.					
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well  Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)					
SW - SE -					
Was a chemical/bacteriological sample submitted to Department?   Yes No					
S If yes, mo/day/yr sample was submitted					
1 mile Water well disinfected? ✓ Yes □ No					
5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other					
CASING JOINTS:  Glued  Clamped  Welded  Threaded					
Casing diameter 5 in to 50 ft Diameter in to ft Diameter in to					
Casing neight above rand surface					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From 50 ft. to 70 ft., From ft. to ft.					
GDAVEL DACK INTEDA	ALS: From 25	t. to	ft., From	ft. t	o ft.
GRAVELTACKINTERV	From f	ii. 10	II., From	ft. 1	to ft.
Fromft. toft., Fromft. toft. ft. doft. ft. do					
Grout Intervals: From 0 ft. to 25 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
Septic tank					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well NONE					
Usertight sewer lines Useepage pit Useedyard Usertilizer storage Uoil well/gas well NONE  Direction from well Distance from well USEPONG TO USE TO U					
FROM TO LITH	OLOGIC LOG	FROM T	O LITHO LO	G (cont.) or PLU	GGING INTERVALS
0 22 TAN CLAY				<u> </u>	CALAVALITE OFFICE
22 35 SANDY BLUE C	LAY				
	TONE SANDY BLUE CL		£		
45 55 BLUE CLAY	77. 2. 1				
55 67 BROKEN LIMES	IONE				
67 70 GRAY SHALE					
	,				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged					
1 Under the function and was completed on (mo/day/year) U9/ZU/ZU 1 and this record is true to the best of the first of the					
1 National Well Contractor's License No. 141 This Water Wall Decord was completed as $(x, y)$					
I under the pusiness name of VVAISON VVELL DRILLING, INC. by (gianotype) (it therefold to be a second to be a s					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
The first water weight and a state of the st					
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					