		R WELL RECORD FO	orm WWC-	5 KSA 82a-				
1 LOCATION OF WATER V			,	ction Number	Township Numb		Range Number	
County: Smith		SE 1/4 NE	1/4	29	<u> </u>	S R	<i>14</i> €(%)	
Distance and direction from nearest town or city street address of well if located within city?								
South Main Athyl, 58/4/mw9								
2 WATER WELL OWNER:						•		
RR#, St. Address, Box # :	South Mour	11000			_		of Water Resources	
City, State, ZIP Code	Athy Kausa	3 66832			Application Nu			
LOCATE WELL'S LOCAT	ION WITH 4 DEPTH OF	COMPLETED WELL	! 9	ft. ELEVAT	TON:			
AN "X" IN SECTION BO: N	Depth(s) Ground	dwater Encountered 1	<i>U</i>	ft. 2.		ft. 3		
ī	I WELL'S STATION	WATER LEVEL . 1.0.1	3.7 ft. 1	pelow land surf	ace measured on mo	/day/yr	17/95	
	' Pum	p test data: Well water						
	NW NE Est. Yield gpm: Well water was ft. after hours pumping gpm							
•	Bore Hole Diameter 8,65. in. to 19							
ž W I	WELL WATER	TO BE USED AS: 5	Public wat	er supply {	3 Air conditioning	11 Injectio	n well	
	1 Domestic				9 Dewatering		(Specify below)	
2M	2 Irrigation	4 Industrial 7	Lawn and	garden on	0 Monitoring well	.,		
1 1 1	Was a chemical	/bacteriological sample sul	mitted to D	epartment? Ye	s(.No)	; If yes, mo/da	y/yr sample was sub-	
<u> </u>	mitted			Wate	er Well Disinfected?	Yes	(No)	
5 TYPE OF BLANK CASIN	IG USED:	5 Wrought iron	8 Conci	ete tile	CASING JOINTS	S: Glued	Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other	(specify below)	Welded		
2 PVC	4 ABS	7 Fiberglass				Threaded.	· · · · · · · · · · · · · · · · · ·	
Blank casing diameter	in. to	ft., Dia						
Casing height above land so	urface Hush Mount	.in., weight		fbs./fi	t. Wall thickness or g	auge No. 🧲	ch 40, 📆	
TYPE OF SCREEN OR PE	RFORATION MATERIAL:		7 P\	/c >	10 Asbesto	s-cement	•	
1 Steel	3 Stainless steel	5 Fiberglass	8 RI	MP (SR)	11 Other (s	specify)		
2 Brass	4 Galvanized steel	6 Concrete tile	9 AE	3S	12 None u	sed (open holi	e)	
SCREEN OR PERFORATION	ON OPENINGS ARE:	5 Gauzed	wrapped		8 Saw cut	11 N	one (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wr	apped		9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
	From	ft. to						
GRAVEL PACK IN	ITERVALS: From	. .3 ft. to		ft., From	1	ft. to		
•	From	ft. to		ft., From	1	ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals: From		ft., From	ft.	to	ft., From	ft. 1	to	
What is the nearest source	•			10 Liveste			ned water well	
1 Septic tank 4 Lateral lines 7 Pit privy				11 Fuel storage 15 Oil well/Gas well				
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)		
3 Watertight sewer lin	es 6 Seepage pit	9 Feedyard			icide storage			
Direction from well?				How man		ONIO INTERN	(4) 0	
FROM TO	LITHOLOGIC		FROM	ТО	PLUG	GING INTERV	ALS	
	of dark brown	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					<u>_</u>	
5 8 0	1111 75 1 2 1 1	1. brown, me ple	/	 				
8 19 S	High clay +	me grained						
	and light Dr	W-v-		-				
<u> </u>	ver le !!							
				+				
				+				
				+				
				-				
 				 				
				+				
				 				
				+				
				++				
7 CONTRACTOR'S OR L								
completed on (mo/day/year)								
Water Well Contractor's License No								
under the business name of	MAXIMTECHA	10LOGIES		by (signat	ure) William	14 Ku	don	
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								