WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Phillpis	Fraction SW 1/4 SW 1/4 SE 1/4 NW 1/4	Section Number Township No. Range Number
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:		
from nearest town or intersection: If at	Latitude: .99.1173 (in decimal degrees)	
412' East of 410 N. Main St.		Longitude: 39.764 (in decimal degrees)
Agra, KS ANL SG-2D		Elevation: .1857. Datum: WGS 84, NAD 83, NAD 27
2 WATER WELL OWNER: CCC/U	SDA/FSA (Steve Gilmore)	Collection Method:
RR#, Street Address, Box #: Stop 0513 Rm 4717-S Indpendence Ave SW		☐ GPS unit (Make/Model: MobleMaper CE)
City, State, ZIP Code : Washir	gton, DC 20250-0513	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
3 LOCATE WELL		Est. Accuracy:
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 30 ft.		
SECTION BOX: Depth(s) Groun	dwater Encountered (1) None	ft. (2) ft. (3) ft.
N WELL'S STAT	IC WATER LEVELft.	below land surface measured on mo/day/yrN/A
Pum	test data: Well water was. NA	ft. after N/A hours pumping N/A gpm
EST. YIELD. N/Agpm. Well water was N/Aft. after N/A hours pumping. N/Ag		ft. after N/A hours pumping N/A gpm
W Bore Hole Diameter 4.25 in. to .30 ft., and in. to		t., andft.
Domestic Discollet Discoll		
SW SE Domestic Feediot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well Soil Gas SandPnt.		
Was a chemical/bacteriological sample submitted to Department? Yes No		
S If yes, mo/day/yr sample was submitted.N/A		
1 mile Water well disinfected? ☐ Yes ☑ No		
5 TYPE OF CASING USED: Steel V PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded		
Casing diameter .1 in. to .29 ft., Diameter in. to ft., Diameter ft.		
Casing height above land surface. 0		
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)		
Brass Galvanized Steel None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From		
From		
GRAVEL PACK INTERVALS: From		
From ft. to ft., From ft. to ft.		
6 GROUT MATERIAL: V Neat cement Cement grout Bentonite Other		
Grout Intervals: From Chios 27. ft. to 25 ft., From Cmt 25. ft. to Surface ft., From ft. to ft. What is the nearest source of possible contamination:		
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)		
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well		
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Grain Elevator		
Direction from well South FROM TO LITHOLOG		from well200'
FROM TO LITHOLOG 12 Silty Clay-Dark Brown	GIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
12 30 Silty Clay-Tight-Light B	rown-Moist	
Sitty Sidy Tight Eight E	TOWN WORK	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged		
under my jurisdiction and was completed on (mo/day/year) .0.7/01/09 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 680 This Water Well Record was completed on the only very 07/10/09		
under the business name of .Delta Environmental by (signature) by		
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and once the suffer answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.		
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdheks.gov/waterwell/index.html.		
KSA 82a-1212 Check: White Copy, We Blue Copy, Pink Copy		

