WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Philipis	Fraction SW 1/4 SW 1/4 SE 1/4 NW 1/4	Section Number Township No. Range Number 27 T 3 S R 16 DE VW
		Global Positioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here . Latitude:		
412' East of 410 N. Main St.		Longitude: 39.764 (in decimal degrees)
Agra, KS ANL SG-2S		Elevation: 1857
2 WATER WELL OWNER: CCC/USDA/FSA (Steve Gilmore)		Collection Method:
RR#, Street Address, Box #: Stop 0513 Rm 4717-S Independence Ave SW City, State, ZIP Code : Washington DC 20250-0513		GPS unit (Make/Model: MobleMaper CE
Washington, DC 20200-0313		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 21		
SECTION BOX: Depth(s) Groundwater Encountered (1) None ft (2) ft (3)		
N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr. N/A		
Pump test data: Well water was. NAft. after. NA hours pumping. N/Agpm		
EST. YIELD. N/Agpm. Well water was. N/Aft. after. N/Ahours pumping. N/Agpm Bore Hole Diameter 4.25in. to .21ft., andin. toft.		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
Sw. SF. Domestic Feedlot Oil field water supply Dewatering Other (Specify below)		
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Soil Gas SandPnt.		
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted N/A		
1 mile Water well disinfected? ☐ Yes ☑ No		
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded		
Casing diameter .1		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel		
Brass Galvanized Steel None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Gauze wrapped Torch cut Drilled holes None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)		
SCREEN-PERFORATED INTERVALS: From 20 ft. to 21 ft., From ft. to ft.		
From		
From		
6 GROUT MATERIAL: ✓ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other		
Grout Intervals: From Chios 18. ft. to 16		
Septic tank		
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well		
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Grain Elevator Direction from well .200! ☐ Grain Elevator ☐ Distance from well .200! ☐ D		
FROM TO LITHOLOG		TO LITHO, LOG (cont.) or PLUGGING INTERVALS
0 12 Silty Clay-Dark Brown	1110111	2
12 21 Silty Clay-Tight-Light Br	own-Moist	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged		
under my jurisdiction and was completed on (mo/day/year) .9.7/01/09 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 680 This Water Well Record was completed on (mg/(ta//year) 97/10/99		
under the business name ofDelta Environmental		
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367		
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .		
KSA 82a-1212 Check: White Copy, W Blue Copy, Pink Copy		

