


1 LOCATION OF WATER WELL: County: Phillips Fraction: NW 1/4 NW 1/4 NW 1/4 Section Number: 35 Township Number: T 3 S Range Number: R 18 E

Distance and direction from nearest town or city street address of well if located within city? 487 3rd St Phillipsburg KS #4 95 96

2 WATER WELL OWNER: Doris Kampfe RR#, St. Address, Box #: 487 3rd St City, State, ZIP Code: Phillipsburg KS 67461 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: 58 ft. WELL'S STATIC WATER LEVEL: 58 ft. below land surface measured on mo/day/yr 7-17-95 Pump test data: Well water was air developed ft. after 1 hours pumping 1 gpm Est. Yield 20 gpm: Well water was air developed ft. after 1 hours pumping 1 gpm Bore Hole Diameter 9 in. to 20 ft., and 8 in. to 25 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ② Irrigation lawn 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded ② PVC 4 ABS 7 Fiberglass 9 Other (specify below) Blank casing diameter 5 in. to 58 ft. Dia. 15 in. to 58 ft. Dia. Casing height above land surface 15 in. weight 229 cft lbs./ft. Wall thickness or gauge No. 214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass ② PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped ③ Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 58 ft. to 68 ft. GRAVEL PACK INTERVALS: From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug Grout Intervals: From 5 ft. to 25 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well ③ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? SE How many feet? 50+

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	55	top soil & clay			
55	60	clay w/ lot of sand			
60	67	clay w/ lot of broken rock			
67	75	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-17-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 165 This Water Well Record was completed on (mo/day/year) 7-18-95 10:00 pm under the business name of Maruhn well Drilling by (signature) LeRoy Maruhn